

# Journal of Chemical Engineering and Material Science

Volume 7 Number 2 July 2015

ISSN 2141-6605



*Academic  
Journals*

## ABOUT JCEMS

The **Journal of Chemical Engineering and Materials Science (JCEMS)** is published monthly (one volume per year) by Academic Journals.

**Journal of Chemical Engineering and Materials Science (JCEMS)** is an open access journal that provides rapid publication (monthly) of articles in all areas of the subject such as semiconductors, high-temperature alloys, Kinetic Processes in Materials, Magnetic Properties of Materials, optimization of mixed materials etc. The Journal welcomes the submission of manuscripts that meet the general criteria of significance and scientific excellence. Papers will be published shortly after acceptance. All articles published in JCEMS are peer-reviewed.

### Contact Us

Editorial Office:

[jcems@academicjournals.org](mailto:jcems@academicjournals.org)

Help Desk:

[helpdesk@academicjournals.org](mailto:helpdesk@academicjournals.org)

Website:

<http://www.academicjournals.org/journal/JCEMS>

Submit manuscript online

<http://ms.academicjournals.me/>

## Editors

**Dr. R. Jayakumar**

*Center for Nanosciences Amrita  
Institute of Medical Sciences and Research  
Centre  
Amrita Vishwa Vidyapeetham University  
Cochin-682 026  
India*

**Prof. Lew P Christopher**

*Center for Bioprocessing Research and  
Development(CBRD)  
South Dakota School of Mines and  
Technology(SDSM&T)  
501 East Saint Joseph Street  
Rapid City 57701 SD  
USA*

**Prof. Huisheng Peng**

*Laboratory of Advanced Materials  
Department of Macromolecular Science  
Fudan University Shanghai 200438  
China*

**Prof. Layioye Ola Oyekunle**

*Department of Chemical Engineering  
University of Lagos Akoka-Yaba  
Lagos Nigeria*

**Dr. Srikanth Pilla**

*Structural Engineering and Geomechanics Program  
Dept of Civil and Environmental Engineering  
Stanford University  
Stanford CA 94305-4020  
USA.*

**Asst Prof. Narendra Nath Ghosh**

*Department of Chemistry,  
Zuarinagar, Goa-403726,  
India.*

**Dr. Rishi Kumar Singhal**

*Department of Physics, University of Rajasthan,  
Jaipur 302055 India.*

**Dr. Daoyun Song**

*West Virginia University  
Department of Chemical Engineering,  
P. O Box 6102, Morgantown, WV 26506,  
USA.*

## Editorial Board

**Prof. Priyabrata Sarkar**

*Department of Polymer Science and  
Technology University of Calcutta  
92 APC Road Kolkata India*

**Dr. Mohamed Ahmed AbdelDayem**

*Department of Chemistry  
College of Science King Faisal University  
Al-Hasa Saudi Arabia*

**Ayo Samuel Afolabi**

*School of Chemical and Metallurgical  
Engineering  
University of the Witwatersrand Johannesburg  
Private Bag 3 Wits 2050 Johannesburg South  
Africa*

**Dr. S. Bakamurugan**

*Institut für Anorganische und Analytische  
Chemie Universität Münster Corrensstrasse  
30 D-48149 Münster Germany*

**Prof. Esezobor David Ehigie**

*Department of Metallurgical and Materials  
Engineering Faculty of Engineering  
University of Lagos, Lagos*

**Dr sunday ojolo**

*Mechanical Engineering Department  
University of Lagos  
Akoka Lagos, Nigeria*

**Prof. Dr. Qingjie Guo**

*College of Chemical Engineering  
Qingdao University of Science and Technology  
Zhengzhou 53 Qingdao 266042 China*

**Dr Ramli Mat**

*Head of Chemical Engineering Department  
Faculty of Chemical and Natural Resources  
Engineering Universiti Teknologi  
Malaysia*

**Prof. Chandan Kumar Sarkar**

*Electronics and Telecommunication Engineering  
Jadavpur University Kolkata India*

**Dr.-Ing. Ulrich Teipel**

*Georg-Simon-Ohm Hochschule Nürnberg  
Mechanische Verfahrenstechnik/  
Partikeltechnologie Wassertorstr. 10  
90489 Nürnberg Germany*

**Dr. Harsha Vardhan**

*Department of Mining Engineering  
National Institute of Technology Karnataka Surathkal  
P.O - Srinivasnagar - 575025 (D.K)  
Mangalore Karnataka State India*

**Dr. Ta Yeong Wu**

*School of Engineering  
Monash University Jalan Lagoon  
Selatan Bandar Sunway 46150  
Selangor Darul Ehsan Malaysia*

**Dr. Yong Gao**

*DENTSPLY Tulsa Dental Specialties  
5100 E. Skelly Dr. Suite 300  
Tulsa Oklahoma USA*

**Dr. Xinli Zhu**

*School of chemical Biological and materials  
engineering the University of Oklahoma  
100 E Boyd St SEC T-335 Norman, OK 73019  
USA*

**ARTICLE**

**Research Article**

**Preparation of phosphoric acid activated carbons from *Canarium Schweinfurthii* Nutshell and its role in methylene blue adsorption** **9**

Adegboyega Surajudeen Olawale, Olusegun Ayoola Ajayi, Michael Sunday Olakunle, Mku Thaddeus Ityokumbul and Sam Sunday Adefila

Full Length Research Paper

## Preparation of phosphoric acid activated carbons from *Canarium Schweinfurthii* Nutshell and its role in methylene blue adsorption

Adegboyega Surajudeen Olawale<sup>1</sup>, Olusegun Ayoola Ajayi<sup>2\*</sup>, Michael Sunday Olakunle<sup>1</sup>, Mku Thaddeus Ityokumbul<sup>3</sup> and Sam Sunday Adefila<sup>4</sup>

<sup>1</sup>Department of Chemical Engineering, Ahmadu Bello University, Zaria, Nigeria.

<sup>2</sup>Department of Chemical and Petroleum Engineering, Afe Babalola University, Ado Ekiti, Ekiti State, Nigeria.

<sup>3</sup>Department of Energy and Mineral Processing, Penn State University, Pennsylvania, U.S.A.

<sup>4</sup>Engineering and Environmental Services Limited, Suite 5 ZM Plaza, Ahmadu Bello Way, Garki 11, Abuja, Nigeria.

Received 30 April, 2015; Accepted 8 July, 2015

Activated carbons were prepared by phosphoric acid activation of *Canarium Schweinfurthii* spent nutshell. The activation conditions for particles with average diameter of 2.36 mm, conducted in nitrogen chamber, were evaluated at 40 and 60% acid concentration, substrate/activating agent (impregnation) ratio of 1:1 to 1:4, activation time of 20 to 60 min and temperatures of 200 and 400°C. The results showed that the yield, BET surface area and adsorption capacities of activated carbon produced increased with impregnation ratio, activation time and temperatures. The activated carbon obtained using 1:4 impregnation ratios at 60 min with 40 wt% acid solution have BET surface area and adsorption capacity of 741 m<sup>2</sup>/g and 8.5 gMB/g Carbon while those for 60wt% acid solution were determined as 779 m<sup>2</sup>/g and 9.2 gMB/g Carbon, respectively.

**Key words:** *Canarium schweinfurthii*, activated carbon, phosphoric acid, methylene blue, impregnation ratio, dyes.

### INTRODUCTION

Paper, dyeing, plastic, and textile industries use dyes for coloring their products. These industries generate large quantity of waste water containing residual dyes, which are often discharged to the environment with or without treatment (Ehrampoush et al., 2011; Sreedhar and Kotaiah, 2006). There are over 100,000 types of dyes with more than  $7 \times 10^5$  tons produced annually (Wang et al., 2008). About 2% of dyes produced are discharged in

effluent during production, while 10 to 20% remains in textile wastewater (Espulgas et al., 2002; Gregorio, 2006). The release of dyes into waters causes immediate visible pollution aside from contamination due to its organic and toxic nature. The presence of these dyes is objectionable because it interferes with light penetration and therefore reduces photosynthetic activity (Weisburger, 2002). Dyes are not readily biodegradable

\*Corresponding author. E-mail: segeaj@gmail.com, molakunles@gmail.com.

Author(s) agree that this article remain permanently open access under the terms of the [Creative Commons Attribution License 4.0 International License](http://creativecommons.org/licenses/by/4.0/)

and their removal from wastewater often involves processes such as floatation, chemical oxidation, precipitation, filtration, electrocoagulation, ozonation and photocatalytic. These processes have found industrial applications in meeting the more stringent legislation regarding maximum allowable dye concentration in discharge wastewater (Wang et al., 2008; Bestani et al., 2008).

Activated carbon adsorption is a process that is widely used for removal of waste from effluents. This application relies on the large surface area of the adsorbent, with its micro-porous structure, resulting in high adsorption capacity. The operation is generally simple to implement and gives high removal efficiency (Ramakrishna and Viraraghavan, 1997; Meyer et al., 1992; Natos et al., 2010). Kant (2012), Kanawade and Gaikwad (2011) and Rahman et al. (2012) identified the negative effects of methylene blue on our environment and proposes application activated carbon as adsorbent.

*Canarium schweinfurthii* is a perennial plant, with oil bearing seeds, which is available abundantly in Nigeria and other parts of the tropics. Its spent nutshell generates a lot of waste that could serve as a reliable feedstock to obtain carbons with good adsorptive properties. Conversion of nutshell from *C. schweinfurthii* to activated carbon would have dual advantages of producing a low cost adsorbent material for environmental protection, while at the same time eliminating the need for land filling, open burning and indiscriminate disposal (Ajayi and Olawale, 2009).

Activated carbon is commonly produced from carbonaceous material via either thermal or chemical activation. In this work, phosphoric acid was chosen as the activating agent in view of its environmental benefits. Chemical activation with phosphoric acid not only reduces tar formation thereby increasing carbon yield (Benadjemia et al., 2011; Shaobih et al., 2005; Lim et al., 2010) it also gives the possibility of developing microporous and/or mesoporous carbon with high specific surface area (Jagtøyen and Derbyshire, 1998).

Accordingly the aim of this work is to study the ability of *C. Schweinfurthii* to serve as a precursor for an effective activated carbon for methylene blue adsorption. The size of methylene blue, would serves as a good probe for the efficiency of the activated carbon developed. (Pelekani and Snoeyink, 2000). The effect of impregnation ratio, activation temperature and time on the characteristic properties of activated carbon developed was also studied.

## EXPERIMENTAL

### Materials

*C. schweinfurthii* nutshell was washed with water and then dried in oven at 60°C for 12 h. The seeds were removed from the *C. schweinfurthii* fruit to make the nutshell oil free (Olawale, 2012).

The nutshell was then washed repeatedly with water and dried at 110°C for 12 h. The dried nutshell was crushed and sieved to obtain particle size fraction of 2.0 to 2.36 mm, which were later stored in air tight container awaiting further use.

### Preparation of activated carbon

Specified mass of the dried nutshell particles were soaked in 100 ml H<sub>3</sub>PO<sub>4</sub> solution (40 and 60% concentration) to get the required impregnation ratios of *C. schweinfurthii* nutshell: H<sub>3</sub>PO<sub>4</sub> of 1:1, 1:2 and 1:4. Impregnation ratio is defined as the ratio of the weight of precursor, that is, weight of dried crushed *C. schweinfurthii* nutshell to the weight of H<sub>3</sub>PO<sub>4</sub>. The liquid/solid mixture was stirred continuously at ambient temperature for 2 h and left to soak for 12 h to allow penetration of the H<sub>3</sub>PO<sub>4</sub> into the *C. schweinfurthii* nutshell (Montane and Torne-Fernandez, 2005). After the stipulated soaking time, the slurry was oven dried at 110°C for 24 h, so as to achieve adsorption of the H<sub>3</sub>PO<sub>4</sub> on to the *C. schweinfurthii* nutshell.

The activation temperature and time for this work was fixed at the lowest possible value, supported by the reported work of Gratuito et al. (2008) and Srinivasakannan and Abu Bakar (2004). They both arrived at optimum activation temperature and time of 416°C and 30 min, respectively, during activation of coconut shell using phosphoric acid, which was also adopted in this work.

The activation of the dried impregnated with phosphoric acid nutshell particles was performed in a batch reactor in nitrogen atmosphere at a heating rate of 10°Cmin<sup>-1</sup>, set to three different temperatures 200, 300 and 400°C for activation times of 20, 40 and 60 min at each activation temperature. Following activation, the samples were cooled in nitrogen atmosphere for 12 h. The product was washed with cold deionized water until phosphate ions were no longer detected by the lead nitrate test. The product was finally air dried at 105°C for 3 h, after which it was ground and characterized.

### Characterization

The products were characterized for yield, BET surface area and adsorptive capacity. The 'yield' of the activated carbon synthesis is defined as the ratio of the mass of activated carbon (after washing and drying) to that of the dried nutshell multiplied by 100. The pH of the samples was determined by placing 1 g of the activated carbon in 20 cm<sup>3</sup> distilled water. The suspension was stirred for 6 h at 250 rpm, after which the clear solution was filtered and its pH was determined using Kent digital pH meter (Model 7055).

The ash, moisture and crude fiber contents and other properties for both the raw material and products were determined as described by AOAC (2010). The BET surface area was determined using water vapor adsorption method described by Adefila et al. (2003). The adsorptive capacities were obtained using methylene blue solution as probe following the method detailed by Raposo et al. (2009).

## RESULTS AND DISCUSSION

### Physical properties and proximate analysis of *C. schweinfurthii* nutshell

As could be seen from Table 1, the *C. schweinfurthii* nutshell could serve as a very good precursor for the production of activated carbon due to its very low value in



**Table 1.** Proximate analysis of *Canarium schweinfurthii* nutshell.

Characteristics	Value (%)
Ash	1.16
Moisture	10.3
Crude fiber	40
Protein	2.6
Lipid	3.27
Carbohydrates	37.23

ash content (1.16%) and very high value of carbon containing constituents (88.64%).

### Production yield

The carbon yield is relatively high compare to physical activation processes. This is an indication of the ability of  $H_3PO_4$  to retain carbon and to avoid the loss of otherwise volatile materials, on one hand. On the other hand,  $H_3PO_4$  activation promotes dehydration and redistribution of biopolymers and also favors the conversion of aliphatic to aromatic compounds, thus increasing the yield of activated carbon (Yakout and Sharaf-el-Deen, 2012). The carbon yield increases as the impregnation ratio was increase at 40 to 60% for temperatures 200 to 400°C and time varying between 20, 40 and 60 min as shown in Figures 1 and 2.

When increasing quantity of acid, it is expected that mass transfer into and within the substrate will be enhanced, leading to higher rate of reaction which manifests in the reduced yield. This observation was also reported by other researchers (Girgis and Ishak, 1999).

### Specific surface area

As depicted in Figure 3, the level of activation and BET surface area increases with acid concentration and activation time at constant temperature (400°C) and impregnation ratio of 1:1, which conforms with the works of Jagtoyen and Derbyshire (1998) and Suarez-Garcia et al. (2004). Based on the result, shown in Figure 3, the activation time period was fixed at 60 min to understudy the effect of activating temperatures, acid concentration and impregnation ratio.

The trend observed in Figure 4 suggested increase in both impregnation ratios and surface area with temperature. The activation temperature was stopped at 400°C following the conclusion made by other researchers on maxima value in specific surface for temperatures ranging from 350 to 500°C for lignocelluloses materials and bituminous coal (Yakout and Sharaf-el-Deen, 2012).

Irrespective of the acid concentration (40 or 60 wt%), products with impregnation ratio of 1:4 gave surface area ranging between 500 and 800  $m^2/g$  which agrees with the works of Girgis and Ishak (1999). Above 200°C, the difference in specific surface area for the same acid ratio was not significantly different. The  $H_3PO_4$  reacting within the internal cellulose structure is assumed to induce a polymerization leading to an enhancement of the pore volume and thus global volume expansion, favoring formation of mesopores (Benadjemia et al., 2011).

### Adsorptive capacity

The adsorption of activated carbon using methylene blue was suggested to occur on specific sites forming monolayer coverage. The higher the BET surface area of the activated carbons and impregnation ratio, the higher the adsorption capacity of methylene blue as shown in Figures 5.

The adsorption capacity was observed to increase by about 3 folds for activated carbons with impregnation ratio of 1:4 compared to those with 1:2 and 1:1. This could be explained by the fact that increased in concentrated  $H_3PO_4$  was able to unblock and enlarge the pores of the activated carbon produced. The higher the concentration of  $H_3PO_4$ , the better the effect of pore enlargement and unblocking. The large pore volume resulted in surface accommodation of the probing material in this case methylene blue. Additionally activation temperature was seen to improve the adsorption capacity of methylene blue, testify to the role of  $P_2O_5$  resulting from the chemical transformation of  $H_3PO_4$  at elevated temperature.

### Conclusion

The present study shows that a viable adsorbent can be prepared from *C. schweinfurthii* nutshell through phosphoric acid activation with significant yield and good surface area. *C. schweinfurthii* is a suitable agro-waste precursor due to its abundance in Nigeria and its present disposal approach is not environmental friendly. The yield, though not strongly influenced by the acid strength has been found to vary between 40 and 60% depending on impregnation ratio and activation temperature. The BET surface area of about 800  $m^2/g$  was obtained at the highest condition of treatment. The adsorption capacity was also found to increase with impregnation time and temperature which peaks at about 8 g of activated carbon per mg of MB.

### Conflict of Interest

The authors have not declared any conflict of interest.






Figure 1. Product yield as a function of activation time, temperature and impregnation ratio for 40% H<sub>3</sub>PO<sub>4</sub>.




Figure 2. Product yield as a function of activation time, temperature and impregnation ratio for 60% H<sub>3</sub>PO<sub>4</sub>.




Figure 3. BET surface area as a function acid strength and activation time at 400°C for 1:1 ratio.




Figure 4. BET surface area as function of acid concentration, temperature at 60 min reaction time.





Figure 5. Adsorptive capacity of methylene blue as a function of impregnation ratio, activation time and temperature at acid strength of 40% (a) and 60% (b).

## REFERENCES

- Adefila SS, Aderemi BO, Ajayi OA and Baderin DA (2003). "Comparative surface area determination using water adsorption method". *Nig. J. Eng.* 11(1):89-97.
- Ajayi OA, Olawale AS (2009). "A Comparative study of Thermal and Chemical Activation of *Canarium schweinfurthii* Nutshell". *J. Appl. Sci. Res.* pp. 2148-2152.
- AOAC (2010). [www.aoac.org/ISPAM/pdf/3.5%20SMMPR%20Guideline%20v12.1.pdf](http://www.aoac.org/ISPAM/pdf/3.5%20SMMPR%20Guideline%20v12.1.pdf), assessed on 13<sup>th</sup> February, 2012.
- Benadjemia M, Milliere L, Reinert L, Douche NB, Duclaux L (2011). "Preparation, characteristics and methylene blue adsorption of phosphoric acid activated carbon from globe artichoke leaves". *J. Fuel Process. Technol.* 92(6):1203-1212.
- Bestani B, Benderdouche N, Benstaali B, Belhakem M, Addou A (2008). "Methylene blue and iodine adsorption onto an activated desert plant." *Bior. Tech.* 99(17):8441-8444.
- Ehrampoush MH, Moussavi GHR, Ghaneian MT, Rahimi S, Ahmadian M (2011). "Removal of methylene blue dye from textile simulated sample using tubular reactor and TiO<sub>2</sub>/UV-C photocatalytic process". *Iran. J. Environ. Health Sci. Eng.* 8(1):35-40.
- Espulgas SJ, Gimenez S, Contreras EP, Rodriguez M (2002). "Comparison of Different Advanced Oxidation Processes for Phenol Degradation". *Water Res.* 36:1034-1042.
- Girgis BS, Ishak MF (1999). "Activated carbons from cotton stalks by impregnation with phosphoric acid". *Mat. Letts.* 39(2):107-114.
- Gratisito MKB, Panyathanmaporn T, Chumnanklang RA, Sirinuntawittaya N, Dutta A (2008). Production of activated carbon from coconut shell: Optimization using response surface methodology. *Bioresour. Technol.* 99:4887-4895.
- Gregorio C (2006). "Non-conventional low-cost adsorbents to dye removal". *Bioresour. Technol.* 97:1061-1085.
- Jagtoyen M, Derbyshire F (1998). "Activated carbons from yellow poplar and white oak by Hydrogen tetraoxophosphate activation". *Carbon* 36:1085-1097.
- Kanawade SM, Gaikwad RW (2011). Removal of Methylene Blue from Effluent by Using Activated Carbon and Water Hyacinth as Adsorbent. *Int. J. Chem. Eng. Applic.* 2(5):317-319.
- Kant R (2012). Textile dyeing industry an environmental hazard. *Nat. Sci.* 4(1):22-26.
- Lim WC, Srinivasakanan C, Balasubramanian N (2010). "Activation of palm shells by phosphoric acid impregnation for high yielding activated carbon". *J. Anal. Appl. Pyrolysis* 88:181-186.
- Meyer V, Carlsson FHH, Aoellemann R (1992). "Decolourisation of textile effluents using a low cost natural adsorbent material. *Water Sci. Technol.* P. 16.
- Montane D, Torne-Fernandez VF (2005). "Activated carbons from lignin: kinetic modeling of the pyrolysis of Kraft lignin activated with phosphoric acid". *Chem. Eng. J.* 106(1):1-12.
- Natos M, Barreiro MF, Gandini A (2010). "Olive stone as a renewable source of biopolyols". *Ind. Crop Prod.* 32:7-12.
- Olawale AS (2012). "Solid-liquid extraction of oils of African elemis (*Canarium schweinfurthii*) fruit. *Agric. E. Int: CIGR J.* 14(2):155-161.
- Pelekani C, Snoeyink VL (2000). "Competitive absorption between atrazine and methylene blue on activated carbon: the importance of pore size distribution". *Carbon* 38:1423-1436.
- Ramakrishna KR, Viraraghavan T (1997). "Dye Removal Using Low Cost Adsorbents". *Wat. Sci. Tech.* 36:189-196.
- Raposo F, De La Rubia MA and Borja R (2009). Methylene blue number as useful indicator to evaluate the adsorptive capacity of granular activated carbon in batch mode: Influence of adsorbate/adsorbent mass ratio and particle size. *J. Hazard. Mater.* 165:291-299.
- Shaobih W, Zhwa ZH, Anthony C, Harghsersht F (2005). "The physical and surface chemical characteristics of activated carbons and the adsorption of methylene blue from waste water". *J. Colloid Inter. Sci.* 284:440-446.
- Sreedhar S, Kotaiah B (2006). "Comparative evaluation of commercial and sewage sludge based activated carbons for the removal of textile dyes from aqueous solutions". *Iran. J. Environ. Health Sci. Eng.* 3:239-246.
- Srinivasakannan C, Abu Bakar MZ (2004). Production of activated carbon from wood sawdust. *Bioresour. Technol.* 27:89-96.
- Suarez-Garcia F, Martinez-Alonso A, Tascon JMD (2004). Activated carbon fibers from Nomex by chemical activation with phosphoric acid. *Carbon* 42:1419-1426.
- Wang XS, Zhou Y, Jiang Y, Sun C (2008). "The removal of basic dyes from aqueous solutions using agricultural by-products". *J. Hazard. Mater.* 157:374-385.
- Weisburger JH (2002). "Comments on the history and importance of aromatic and heterocyclic amines in public health". *Mat. Res.* pp. 506-507, 9-20.
- Yakout SM, Sharaf-el-Deen G (2012). "Characteristics of activated carbon prepared by phosphoric acid activation of olive stones". *Arab. J. Chem.* doi:10.1016/j.arabjc.2011.12.002



The background of the entire page is a photograph of an industrial chemical plant. It features large cylindrical storage tanks, a complex network of pipes, and structural steel beams. The lighting is somewhat dim, and the overall color palette is dominated by greys, blues, and greens. The image has rounded corners at the top and bottom.

# Journal of Chemical Engineering and Material Science

## Related Journals Published by Academic Journals

- *Journal of Engineering and Technology Research*
- *International Journal of Water Resources and Environmental Engineering*
- *Journal of Civil Engineering and Construction Technology*
- *International Journal of Computer Engineering Research*
- *Journal of Electrical and Electronics Engineering Research*
- *Journal of Engineering and Computer Innovations*
- *Journal of Mechanical Engineering Research*
- *Journal of Petroleum and Gas Engineering*

**academicJournals**