

Journal of Civil Engineering and Construction Technology

Volume 7 Number 5 October 2016

ISSN 2141-2634



*Academic
Journals*



ABOUT JCECT

Journal of Civil Engineering and Construction Technology (ISSN 2141-2634) is published monthly (one volume per year) by Academic Journals.

Journal of Civil Engineering and Construction Technology (JCECT) is an open access journal that provides rapid publication (monthly) of articles in all areas of the subject such as surveying, environmental engineering, hydrology, soil mechanics, shear moments and forces etc. The Journal welcomes the submission of manuscripts that meet the general criteria of significance and scientific excellence. Papers will be published shortly after acceptance. All articles published in JCECT are peer-reviewed.

Contact Us

Editorial Office: jcect@academicjournals.org

Help Desk: helpdesk@academicjournals.org

Website: <http://www.academicjournals.org/journal/JCECT>

Submit manuscript online <http://ms.academicjournals.me/>

Editors

Dr . George Besseris

*El of Piraeus, Greece
Argyrokastrou 30, Drosia, 14572,
Attica Greece*

Prof. Xiaocong He

*Faculty of Mechanical and Electrical Engineering
Kunming University of Science and Technology
253 Xue Fu Road, Kunming
China*

Prof. Jean Louis Woukeng Feudjio

*Department of Mathematics and Computer Science
University of Dschang, P.O. Box 67 Dschang
Cameroon*

Dr. P.Rathish Kumar

*Department of Civil Engineering,
National Institute of Technology, Warangal 506 004
Andhra Pradesh, India. PhNo
India*

Prof. Waiel Fathi Abd EL-Wahed

*Operations Research & Decision Support
Department
Faculty of Computers and Information
El-Menoufia University, Shibeh EL-Kom
Egypt*

Prof. JM Ndambuki

*Department of Civil Engineering and Building
Vaal University of Technology
Private Bag X021
Vanderbijlpark 1900
South Africa*

Dr. Dipti Ranjan Sahoo

*Department of Civil Engineering
Indian Institute of Technology
Hauz Khas, New Delhi-110016,
India.*

Dr. Messaoud Saidani

*Faculty Postgraduate Manager
Faculty of Engineering and Computing
Coventry University
Coventry CV1 5FB, England
UK.*

Dr. Mohammad Arif Kamal

*Department of Architecture
Zakir Hussain College of Engineering Technology
Aligarh Muslim University
Aligarh -202002
INDIA*

Editorial Board

Dr. Ling Tung-Chai,

*The Hong Kong Polytechnic University,
Department of Civil and Structural Engineering,
Faculty of Construction and Land Use,
HungHom, Kowloon, Hong Kong.*

Dr. Miguel A. Benítez,

*Project Manager,
Basque Center for Applied Mathematics (BCAM),
Bizkaia Technology Park, Building 500,
E-48160 Derio, Basque Country, Spain.*

Dr. Shehata Eldabie Abdel Raheem,

*Structural Engineering,
Civil Engineering Department,
Faculty of Engineering,
Assiut University, Assiut 71516,
Egypt.*

Dr. Zhijian Hu,

*Department of Road and Bridge Engineering,
School of Communication,
Wuhan University of Science and Technology,
Wuhan, 430063, China.*

Dr. Mohd Rasoul Suliman,

*Prince Abdullah Bin Ghazi Faculty of Science & Information
Technology, Al-Balqa Applied University, Jordan.*

Dr. Paul Scarponcini PE,

*Geospatial and Civil Software Standards,
66 Willowleaf Dr., Littleton, CO 80127,
USA.*

Dr. Rita Yi Man Li,

*Hong Kong Shue Yan University
North Point, Hong Kong.*

Dr. Alaa Mohamed Rashad,

*Building Materials Research and Quality Control Institute,
Housing & Building National Research
Center, 87 El-Tahrir St., Dokki, Giza 11511,
P.O.Box: 1770 Cairo, Egypt.*

Dr. Alaa Mohamed Rashad Abdel Aziz Mahmoud,

*Housing and Building National Research center,
87 El-Tahrir St., Dokki, Giza 11511,
P.O.Box: 1770 Cairo, Egypt.*

Dr. Nikos Pnevmatikos,

*Greek Ministry of Environment,
Urban Planning and Public Works,
Department of Earthquake Victims and Retrofitting
Services, Greece.*

Prof. Karima Mahmoud Attia Osman,

6 Zahraa Naser City, Cairo, Egypt.

Dr. Lim Hwee San,

*99E-3A-10, I-Regency Condominium, Jalan Bukit Gambir,
11700, Penang, Malaysia.*

Dr. Jamie Goggins,

*Civil Engineering, School of Engineering and Informatics,
National University of Ireland, Galway, Ireland.*

Dr. Hossam Mohamed Toma,

*King Abdullah Institute for Research and Consulting Studies,
King Saud University, P.O.Box 2454,
Riyadh 11451, Saudi Arabia.*

Dr. Depeng Chen,

*School of Civil Engineering,
Anhui University of Technology,
59#, Hudong Road, Maanshan, 243002,
China.*

Dr. Srinivasan Chandrasekaran,

*Room No. 207, Dept of Ocean Engineering ,
Indian Institute of Technology Madras, Chennai,
India.*

Prof. Amir Alikhani,

*Ministry of Oil, Harbour organization, and minister of
Energy Tehran, Iran.*

Dr. Memon Rizwan Ali,

*Department of Civil Engineering,
Mehran University of Engineering & Technology,
Jamshoro.*

Prof. Murat Dicleli,

*Department of Engineering Sciences,
Middle East Technical University,
06531 Ankara, Turkey.*

Instructions for Author

Electronic submission of manuscripts is strongly encouraged, provided that the text, tables, and figures are included in a single Microsoft Word file (preferably in Arial font).

The **cover letter** should include the corresponding author's full address and telephone/fax numbers and should be in an e-mail message sent to the Editor, with the file, whose name should begin with the first author's surname, as an attachment.

Article Types

Three types of manuscripts may be submitted:

Regular articles: These should describe new and carefully confirmed findings, and experimental procedures should be given in sufficient detail for others to verify the work. The length of a full paper should be the minimum required to describe and interpret the work clearly.

Short Communications: A Short Communication is suitable for recording the results of complete small investigations or giving details of new models or hypotheses, innovative methods, techniques or apparatus. The style of main sections need not conform to that of full-length papers. Short communications are 2 to 4 printed pages (about 6 to 12 manuscript pages) in length.

Reviews: Submissions of reviews and perspectives covering topics of current interest are welcome and encouraged. Reviews should be concise and no longer than 4-6 printed pages (about 12 to 18 manuscript pages). Reviews are also peer-reviewed.

Review Process

All manuscripts are reviewed by an editor and members of the Editorial Board or qualified outside reviewers. Authors cannot nominate reviewers. Only reviewers randomly selected from our database with specialization in the subject area will be contacted to evaluate the manuscripts. The process will be blind review.

Decisions will be made as rapidly as possible, and the journal strives to return reviewers' comments to authors as fast as possible. The editorial board will re-review manuscripts that are accepted pending revision. It is the goal of the ERR to publish manuscripts within weeks after submission.

Regular articles

All portions of the manuscript must be typed double-spaced and all pages numbered starting from the title page.

The Title should be a brief phrase describing the contents of the paper. The Title Page should include the authors' full names and affiliations, the name of the corresponding author along with phone, fax and E-mail information. Present addresses of authors should appear as a footnote.

The Abstract should be informative and completely self-explanatory, briefly present the topic, state the scope of the experiments, indicate significant data, and point out major findings and conclusions. The Abstract should be 100 to 200 words in length. Complete sentences, active verbs, and the third person should be used, and the abstract should be written in the past tense. Standard nomenclature should be used and abbreviations should be avoided. No literature should be cited.

Following the abstract, about 3 to 10 key words that will provide indexing references should be listed.

A list of non-standard **Abbreviations** should be added. In general, non-standard abbreviations should be used only when the full term is very long and used often. Each abbreviation should be spelled out and introduced in parentheses the first time it is used in the text. Only recommended SI units should be used. Authors should use the solidus presentation (mg/ml). Standard abbreviations (such as ATP and DNA) need not be defined.

The Introduction should provide a clear statement of the problem, the relevant literature on the subject, and the proposed approach or solution. It should be understandable to colleagues from a broad range of scientific disciplines.

Materials and methods should be complete enough to allow experiments to be reproduced. However, only truly new procedures should be described in detail; previously published procedures should be cited, and important modifications of published procedures should be mentioned briefly. Capitalize trade names and include the manufacturer's name and address. Subheadings should be used. Methods in general use need not be described in detail.

Results should be presented with clarity and precision. The results should be written in the past tense when describing findings in the authors' experiments. Previously published findings should be written in the present tense. Results should be explained, but largely without referring to the literature. Discussion, speculation and detailed interpretation of data should not be included in the Results but should be put into the Discussion section.

The Discussion should interpret the findings in view of the results obtained in this and in past studies on this topic. State the conclusions in a few sentences at the end of the paper. The Results and Discussion sections can include subheadings, and when appropriate, both sections can be combined.

The Acknowledgments of people, grants, funds, etc should be brief.

Tables should be kept to a minimum and be designed to be as simple as possible. Tables are to be typed double-spaced throughout, including headings and footnotes. Each table should be on a separate page, numbered consecutively in Arabic numerals and supplied with a heading and a legend. Tables should be self-explanatory without reference to the text. The details of the methods used in the experiments should preferably be described in the legend instead of in the text. The same data should not be presented in both table and graph form or repeated in the text.

Figure legends should be typed in numerical order on a separate sheet. Graphics should be prepared using applications capable of generating high resolution GIF, TIFF, JPEG or Powerpoint before pasting in the Microsoft Word manuscript file. Tables should be prepared in Microsoft Word. Use Arabic numerals to designate figures and upper case letters for their parts (Figure 1). Begin each legend with a title and include sufficient description so that the figure is understandable without reading the text of the manuscript. Information given in legends should not be repeated in the text.

References: In the text, a reference identified by means of an author's name should be followed by the date of the reference in parentheses. When there are more than two authors, only the first author's name should be mentioned, followed by 'et al'. In the event that an author cited has had two or more works published during the same year, the reference, both in the text and in the reference list, should be identified by a lower case letter like 'a' and 'b' after the date to distinguish the works.

Examples:

Abayomi (2000), Agindotan et al. (2003), (Kelebeni, 1983), (Usman and Smith, 1992), (Chege, 1998;

1987a,b; Tijani, 1993,1995), (Kumasi et al., 2001)
References should be listed at the end of the paper in alphabetical order. Articles in preparation or articles submitted for publication, unpublished observations, personal communications, etc. should not be included in the reference list but should only be mentioned in the article text (e.g., A. Kingori, University of Nairobi, Kenya, personal communication). Journal names are abbreviated according to Chemical Abstracts. Authors are fully responsible for the accuracy of the references.

Examples:

Chikere CB, Omoni VT and Chikere BO (2008). Distribution of potential nosocomial pathogens in a hospital environment. *Afr. J. Biotechnol.* 7: 3535-3539.

Moran GJ, Amii RN, Abrahamian FM, Talan DA (2005). Methicillinresistant *Staphylococcus aureus* in community-acquired skin infections. *Emerg. Infect. Dis.* 11: 928-930.

Pitout JDD, Church DL, Gregson DB, Chow BL, McCracken M, Mulvey M, Laupland KB (2007). Molecular epidemiology of CTXM-producing *Escherichia coli* in the Calgary Health Region: emergence of CTX-M-15-producing isolates. *Antimicrob. Agents Chemother.* 51: 1281-1286.

Pelczar JR, Harley JP, Klein DA (1993). *Microbiology: Concepts and Applications.* McGraw-Hill Inc., New York, pp. 591-603.

Short Communications

Short Communications are limited to a maximum of two figures and one table. They should present a complete study that is more limited in scope than is found in full-length papers. The items of manuscript preparation listed above apply to Short Communications with the following differences: (1) Abstracts are limited to 100 words; (2) instead of a separate Materials and Methods section, experimental procedures may be incorporated into Figure Legends and Table footnotes; (3) Results and Discussion should be combined into a single section.

Proofs and Reprints: Electronic proofs will be sent (e-mail attachment) to the corresponding author as a PDF file. Page proofs are considered to be the final version of the manuscript. With the exception of typographical or minor clerical errors, no changes will be made in the manuscript at the proof stage.

Fees and Charges: Authors are required to pay a \$550 handling fee. Publication of an article in the Journal of Civil Engineering and Construction Technology is not contingent upon the author's ability to pay the charges. Neither is acceptance to pay the handling fee a guarantee that the paper will be accepted for publication. Authors may still request (in advance) that the editorial office waive some of the handling fee under special circumstances.

Copyright: © 2016, Academic Journals.

All rights Reserved. In accessing this journal, you agree that you will access the contents for your own personal use but not for any commercial use. Any use and or copies of this Journal in whole or in part must include the customary bibliographic citation, including author attribution, date and article title.

Submission of a manuscript implies: that the work described has not been published before (except in the form of an abstract or as part of a published lecture, or thesis) that it is not under consideration for publication elsewhere; that if and when the manuscript is accepted for publication, the authors agree to automatic transfer of the copyright to the publisher.

Disclaimer of Warranties

In no event shall Academic Journals be liable for any special, incidental, indirect, or consequential damages of any kind arising out of or in connection with the use of the articles or other material derived from the JCECT, whether or not advised of the possibility of damage, and on any theory of liability.

This publication is provided "as is" without warranty of any kind, either expressed or implied, including, but not limited to, the implied warranties of merchantability, fitness for a particular purpose, or non-infringement. Descriptions of, or references to, products or publications does not imply endorsement of that product or publication. While every effort is made by Academic Journals to see that no inaccurate or misleading data, opinion or statements appear in this publication, they wish to make it clear that the data and opinions appearing in the articles and advertisements herein are the responsibility of the contributor or advertiser concerned. Academic Journals makes no warranty of any kind, either express or implied, regarding the quality, accuracy, availability, or validity of the data or information in this publication or of any other publication to which it may be linked.

ARTICLE

Strengthening of existing security buildings against vehicle bomb using fluid viscous dampers, in Egypt	37
Islam M. Ezz El-Arab	

Full Length Research Paper

Strengthening of existing security buildings against vehicle bomb using fluid viscous dampers, in Egypt

Islam M. Ezz El-Arab

Department of Structural Engineering, Tanta University, Egypt.

Received 25 July, 2016; Accepted 19 October, 2016

This paper presents nonlinear numerical simulation of air blast loading with an over pressure level (500 kg TNT) with a different standoff distance of 10, 20, and 50 m to evaluate the effectiveness of Fluid Viscous Dampers (FVD) as new strengthening techniques to reduce blast loading responses on the existing reinforcement concrete buildings. Taking into consideration, most of the security buildings in Middle East, especially in Egypt, during the last three decades, had suffered many blast attacks. This paper presents nonlinear numerical modeling to study the effect and performance comparisons of a conventional structural building frame system with and without FVD. Simulation results indicate that FVD provide a cost-effective way to greatly improve the performance of structural building frames under blast loading.

Key words: Air blast loading, security building, strengthening of exciting building, fluid dampers, vehicle bomb.

INTRODUCTION

In buildings lifetime, building structures could be exposed to extreme natural phenomena (earthquakes, tornados, fire, natural floods) and anthropogenic phenomena (blast or impact). Structures are not usually designed for extreme loadings and when such events occur, it can lead to catastrophic failure. Recently, terrorist attacks targeted security and important buildings led to structural collapse, with important human lives and buildings damages. The term "progressive collapse" refers to the development of an initial local failure (TM 5-1300, 1990; Jankowiak and Tomasz, 2005), which could lead to local or total crush. The main characteristic of progressive collapse is the significant disproportion between initial phase and the final state. Vehicle bomb is one of the famous and repeated ways to attack security buildings that has been a feature of campaigns waged by terrorist

organizations throughout the world.

A bomb explosion inside or directly beside a building can cause catastrophic damage to the building's external and internal structural frames, collapsing of walls, cladding, facades, and shutting down of critical life-safety systems. There are many rezones beyond the casualties and injuries among a building's occupants such as direct blast-effects and structural collapse.

The progressive collapse became an interesting topic for building designers and researchers after the partial collapse of the Ronan Point block in London 1964 and the importance of that subject has highly increased with recent terrorist activities throughout the world. Extreme events as blast and impact, considered improbable in the past, were moved to credible events, having a finite probability of occurrence (Lee et al., 1973; Zhongqi et al.,

E-mail: islamezzelarb@yahoo.com.

Author(s) agree that this article remain permanently open access under the terms of the [Creative Commons Attribution License 4.0 International License](https://creativecommons.org/licenses/by/4.0/)




Figure 1. Blast loads effects on building.




Figure 2. Time history function of blast wave pressure on building.

2004).

Figure 1 presents conventional truck bomb with the blast effect pressure on buildings. The major effective parameters can be defined by charge weight of TNT and standoff distance between the blast source and building. Blast wave instantaneously increases to a value of pressure above the ambient atmospheric pressure. Side-on over pressure decays as the shock wave extends outward from explosion source. After a short time, the pressure behind the front side of the building may drop below the ambient pressure. Suction wave is also accompanied by high suction winds that carry the debris for long distance away from the explosion source (Longinow and Mniszewski, 1996).

Air blast wave's characteristics are found to be affected by physical properties of the explosion source. Figure 2 shows a typical blast pressure profile. At the arrival time t_A , following the explosion, pressure at that position suddenly increases to peak value of over pressure, P_{so} , over the ambient pressure P_o . The pressure then decays to ambient level at time t_d , then decays further to an under pressure P_{so}^- (creating a partial vacuum) before eventually returning to ambient conditions at time $t_d + t_d^-$. The quantity of P_{so} is referred to the peak value of overpressure (side-on) (TM 5-1300, 1990).

All blast parameters are primarily dependent on the amount of energy released by a detonation in the form of a blast wave and the distance from the explosion.



Figure 3. General view of Directorate of Security in Daqahlia Government.

A universal normalized description of the blast effects can be given by scaling distance relative to $(E/P_o)^{1/3}$ and scaling pressure relative to P_o , where E is the energy release (kJ) and P_o the ambient pressure. For convenience, however, it is general practice to express the basic explosive input or charge weight as an equivalent mass of TNT. Results are then given as a function of the dimensional distance parameter (scaled distance) $Z = R/W^{1/3}$, where R is the actual effective distance from the explosion, W is generally expressed in kilograms. Scaling laws provide parametric correlations between a particular explosion and a standard charge of the same substance (TM 5-855-1, 1986).

SECURITY BUILDING IN EGYPT: STUDY CASE

Until 1997, security buildings were developed by the Ministry of Interior in all Provinces in Egypt. After 2000, typical projects have been prepared by the General Authority for Security Buildings (GASB) with the increase in terrorist attacks rates resorted (GASB) of the Egyptian Interior Ministry of the Interior. Provincial directorates have the responsibility for construction supervision of these security buildings. Although, these typical projects display minor differences from one province to another, they are architecturally similar.

GASB has divided security buildings into seven models. This classification was based on two main items. The first is the capacity and function of building; while the second is the security level that depends on the construction site.

The general and common characteristics of mid-security level buildings designed by GASB are as follows:

(1) The load-bearing system of these buildings is

composed of a reinforced concrete column and beam system with or without shear walls.

(2) Interior Ministry Buildings are designed and constructed in accordance with ECP- 201 (2007) for loading and ECP-203 (2008) for reinforcement concrete design.

(3) Spaces inside the buildings are created through non-load bearing brick walls.

In this research, the middle of Delta Region in Egypt has been chosen as an objective of research, where all security buildings are classified as mid-security level of buildings. In addition, most of these buildings were built based on old criteria put into consideration, that is, the security requirements in terms of the structural design of buildings. The case study is a directorate of security that consists of a basement, ground floor, and four typical floors, located in Daqahlia Governor (Middle of Delta, located in North of Egypt).

Figure 3 shows photos of Directorate of Security (case study), which recently suffered a car bombing. This case study was chosen to represent a wide range of buildings located in middle of Delta region. This will enable the preparation of 3D finite element models for comparison with and without Fluid Viscous Dampers (FVD) strengthening techniques due to the different level of blast loads (500 kg TNT) with a different distance a building (10, 20, and 50 m). The statistical system of this public security building is normal skeleton reinforcement concrete building beam and columns system without a shear wall where this building was constructed 1975. Figure 4 presents general architectural and structural layout of typical floors.

Concrete material modelling properties

Under dynamic load conditions, the mechanical properties of concrete have different significant changes compared to concrete under static loads. Figure 5 presents stress strain curve of concrete under static and dynamic loads, respectively. The stresses that are sustained for a certain period of time under dynamic conditions may gain values that are remarkably higher than the static compressive strength. Strength magnification factors as high as 4 in compression and up to 6 in tension for strain rates in the range of 10^2 to 10^5 s⁻¹ have been reported (Grote et al., 2001).

The concrete's natural characteristics are presented in Table 1, used in the finite element modeling case study of security building which is fully constructed of reinforcement concrete as shown in Figure 4 as frame skeleton reinforcement concrete structures.

Finite element modelling

In the finite element modeling, the original ordinary




Figure 4. Architectural and Structural plan of case study, (Directorate of Security of Daqahlia).




Figure 5. Stress-strain curves of concrete at different strain-rates (Ngo et al., 2004a).

Table 1. Material properties of the RC structure (Jankowiak and Tomasz, 2005).

The parameters of CDP model	Value
Young's modulus E (GPa)	19.7
Poisson's ratio ν	0.19
Concrete strength (Mpa) (Cube)	30
β	38°
Flow / potential eccentricity (ε)	1
$\sigma_{b0} / \sigma_{c0}$	1.12
K_C	0.666

Table 2. Modeling of TNT explosive parameters [JWL parameters]

Parameter	Value
Detonation Wave Speed, C_d	6930 m/s
A	373.8 GPa
B	3.747 GPa
R ₁	4.15
R ₂	0.9
ω	0.35
The Density of The Explosive ρ_0	1630 kg/m ³
Initial Specific Energy E_{m0}	3.63 Joule/kg

building of the case study was modeled in accordance with the nonlinear explicit code LS-DYNA (2002), which takes into consideration material nonlinearity and geometric nonlinearity (Stewart and Morrill, 2015). The super structure was simulated as reinforcement skeleton structure system beams and columns as frame element, for slabs was assumed as shell elements (solid slabs) with diaphragm in the orthogonal direction of horizontal expected motion. The soil structural interaction was neglected and all columns in foundation level have fixed boundary condition. The explosive charge (TNT) is modeled using the Jones Wiilkens-Lee (JWL) equation of state. It simulates the pressure generated by explosion of the detonation product (Lee et al., 1973). The parameters of the TNT charge with the properties presented in Zhongqi et al. (2004) are listed in Table 2.

In this study, the security building was chosen as case study to be exposed of the explosive pressure force of 500 kg TNT by offering two proposals; in the first proposal, the security building, which is the original state of the building, while the second proposal will address the same building in the same conditions and assumptions made using FVD as a way of strengthening the building against the impact generated by the forces of the explosion.

Figure 6 presents general view of the Taylor FVD, which was 60 and 20 pieces, erected from ground up to roof level in X Shape for longitudinal and transversal

direction, respectively. Table 3 is the general information Taylor FVD (Miyamoto and Taylor, 2016).

Due to the FVD, the overall structural additional damping ration was increased in longitudinal and transversal direction of exciting building by 2.21 and 2.36%, respectively. Some cross brace configurations were used due to limited space and FVD were used in locations where there was no space for a brace but additional stiffness was needed.

$$\Phi = K_{\varepsilon\phi\phi} \cdot v + Xu^\alpha \quad (1)$$

where K_{eff} = equivalent stiffness of the liquid flexible unit; C = damping coefficient; u = the displacement of the piston rod; \dot{u} = the motion velocity of the piston rod; and α = velocity exponent.

INTERPRETATION OF NUMERICAL ANALYSIS RESULTS

Figures 7 and 8 present over stress at the case study columns if the corner column and edge column in edge column in transversal direction were completely burst, respectively due to blast loading with explosion loading rate 500 TNT at different standoff distance of 50, 20, and 10 m for the structure.

After destroying the column, the efforts that were initially




Figure 6. (a) Cross section of Taylor Fluid Viscous Damper, FVD; (b and c) Arrangement of Taylor FVD in Longitudinal and Transversal direction of case study, respectively.

Table 3. General information on damper parameter.

No.	types	Stiffness (kN/m)	Vel. Exp. α	C (kN.(s/m) α)	F (kN)	D (mm)	Qua.
1	FVD	700	0.3	3000	1000	±100	80

undertaken by this column are redistributed to the adjacent beams through the slab and then to the next columns. The bending moments in the beams connected to the considered column, having an initial negative value, become positive after the removal event. Along with the slab, the beams redistribute a part of the extra loads to the adjacent columns.

Figure 9 presents the blasting loads effect of loading rate 500 kg TNT at standoff 50 m distance from the structural building. Figure 9a, b, and c presents the axial forces reaction redistribution due to explosion corner, transversal, and longitudinal, respectively.

In Figure 9a, b, and c, the axial force before the event of explosion and the axial force of columns after explosion present the extra load value and percentages for the others two columns. The same figures show the values of axial loads present with FVD, which was erected as presented in Figure 6b and c.

The axial force of adjacent columns in longitudinal and transversal directions is increasing by 16.8 and 25.9%, respectively as shown in Figure 8a. In case of erecting FVD as facade bracing, the increase of axial force for the same columns will be 6.3 and 9.6% with decrease percentages of 10 to 15%, due to the application of FVD




Figure 7. Case of corner column removal.




Figure 8. Middle column of short side of structure removal case.

in the redistribution of exploded corner column, as well as, absorption of force of air blasting.

Figures 10 and 11 present the blasting of loading rate of 500 kg TNT with 20 and 10 m standoff distances, respectively. For the cases, Figure 8a, b, and c present the axial force increasing percentages of the remaining columns in case of explosion corner, adjacent column of longitudinal, and transversal columns, respectively; for exciting skeleton security building (case study) as per the conventional system, without and with FVD for strengthening the building.

Axial forces percentage of conventional system is bigger than 25% with standoff distance 10 m compared to

20 m standoff distance as shown in Figures 10 and 11, respectively.

The increasing rate is not linear, where blast loading effects on structural members may produce both local and global responses associated with different failure modes. The type of structural response depends mainly on the loading rate, the orientation of the target with respect to the direction of the blast wave propagation and boundary conditions. The general failure modes associated with blast loading can be flexure, direct shear or punching shear. Local responses are characterized by localized explosion of columns, and generally, result from the close-in effects of explosions, while global




Figure 9. Redistribution value of columns axial forces of corner, adjacent longitudinal and transversal directions, respectively (500 kg TNT at standoff distance 50 m).




Figure 10. Redistribution value of columns axial forces of corner, adjacent longitudinal and transversal directions, respectively (500 kg TNT at standoff distance 20 m).




Figure 11. Redistribution value of columns axial forces of corner, adjacent longitudinal and transversal directions, respectively (500 kg TNT at standoff distance 10 m).

responses are typically manifested as flexural failure.

The close-in effect of explosion may cause a localized shear or a flexural failure at the closest structural elements. This depends mainly on the distance between the source of the explosion and the target, and the relative strength/ductility of the structural elements. The localized shear failure takes place in the form of a localized punching and an explosion, which produces low and high-speed fragments.

Figures 9, 10, and 11 present the effect of the Fluid Viscous Damper upon erecting it as a façade bracing in the longitudinal and transversal directions of exciting security building; the air blasting loads effects at all different standoff distance 50, 20, and 10 m will be decreased where FVD is being worked as an energy dissipation devices. Also, it succeeded to be working into the redistribution of straining action on the other columns through horizontal elements like slabs and beams, which efficiency improve the overall structural performance under blasting loads as compared to conventional systems.

CONCLUSION

This paper numerically investigated the behavior of conventional skeleton structural system of the security buildings in Egypt as case study subjected to a high level of air blast loading (500 kg TNT), with different standoff distances 50, 20, and 10 m as compared to the same case study with FVD as strengthening tools.

(1) For high risks facilities such as security buildings in Egypt, design consideration against extreme events (bomb blast and vehicle bombs) is very important to taken into consideration. Egyptian code of provisions on progressive collapse prevention should be included in the current Egyptian building regulations and design standards where it was missing in Egyptian codes.


(2) Fluid viscous damper as supplements devices should be succeeded to reduce the overall axial force on the adjacent columns of destroyed columns by average percentages of 10 to 17%, for the different standoff distances of blasting loads. FVD is considered effective strengthening technique. FVD worked with the geometrical configuration of the model and the reinforcement position allowed for effort redistribution, so that the collapse can be avoided, which proved to be an effective technique especially for exciting security buildings.

Conflict of interest

The author has not declared any conflict of interests.

REFERENCES

- ECP-201 Permanent Committee (2008). ECP-201:1993, ECP-201:2003, and ECP-201:2008 - Egyptian Code for calculating loads and forces in structural work and masonry, HBRC, Giza.
- ECP-203 Permanent Committee (2007). ECP-203:2007- Egyptian Code for design and construction of concrete structures, HBRC, Giza.
- Grote D, Park S, Zhou M (2001). Dynamic behavior of concrete at high strain rates and pressures. *J. Impact Eng.* 25:869-886. Pergamon Press, New York.
- Jankowiak T, Tomasz L (2005). Identification of parameters of concrete damage plasticity constitutive model. *Foundations of Civil and Environmental Engineering* 6(1):53-69.
- Lee E, Finger M, Collins WJWL (1973). Equations of state coefficient for high explosives, in Lawrence Livermore Laboratory, Livermore, Calif, UCID-16189.
- Longinow A, Mniszewski KR (1996). Protecting buildings against vehicle bomb attacks", *Practice Periodical on Structural Design and Construction*, ASCE, New York, pp. 51-54.
- LS-DYNA Version 960 (2002). Livermore Software Technology Corporation.
- Miyamoto KH, Taylor DP (2016). Structural control of dynamic blast loading using fluid viscous dampers, Technical report.
- Stewart LK, Morrill KB (2015). Residual capacity prediction of blast-loaded steel columns using physics-based fast running models. *Int. J. Safety Security Eng.* 5(4):289-303.
- Taylor Fluid Viscous Dampers FVD, The world leader in innovative shock and vibration control (<http://taylordevices.com/>).
- TM 5-1300 (1990). The Design of Structures to Resist the Effects of Accidental Explosions, Technical Manual, US Department of the Army, Navy, and Air Force, Washington DC.
- TM 5-855-1 (1986). Fundamentals of Protective Design for Conventional Weapons, U.S. Department of the Army, Washington DC.
- Zhongqi W, Yong L, Hong H (2004). Numerical Investigation of Effects of Water Saturation on Blast Wave Propagation in Soil Mass. *J. Eng. Mech.* 130(5):551-561.



Journal of Civil Engineering and Construction Technology

Related Journals Published by Academic Journals

- *International Journal of Computer Engineering Research*
- *Journal of Electrical and Electronics Engineering Research*
- *Journal of Engineering and Computer Innovations*
- *Journal of Petroleum and Gas Engineering*
- *Journal of Engineering and Technology Research*
- *Journal of Civil Engineering and Construction Technology*

academicJournals