



# International Journal of Water Resources and Environmental Engineering

Volume 9 Number 6 June 2017

ISSN-2141-6613



*Academic  
Journals*

## ABOUT IJWREE

**The International Journal of Water Resources and Environmental Engineering** is published monthly (one volume per year) by Academic Journals.

**International Journal of Water Resources and Environmental Engineering (IJWREE)** is an open access journal that provides rapid publication (monthly) of articles in all areas of the subject such as water resources management, waste management, ozone depletion, Kinetic Processes in Materials, strength of building materials, global warming etc. The Journal welcomes the submission of manuscripts that meet the general criteria of significance and scientific excellence. Papers will be published shortly after acceptance. All articles published in IJWREE are peer-reviewed.

### Contact Us

**Editorial Office:** [ijwree@academicjournals.org](mailto:ijwree@academicjournals.org)

**Help Desk:** [helpdesk@academicjournals.org](mailto:helpdesk@academicjournals.org)

**Website:** <http://www.academicjournals.org/journal/IJWREE>

**Submit manuscript online** <http://ms.academicjournals.me/>

## Editors

**Prof. T. Murugesan**

*Universiti Teknologi PETRONAS, Malaysia  
Specialization: Chemical Engineering  
Malaysia.*

**Dr. Sadek Z Kassab**

*Mechanical Engineering Department, Faculty of  
Engineering, Alexandria University, Alexandria,  
Egypt  
At Present: Visting Professor, Mechanical Engineering  
Department, Faculty of Engineering & Technology,  
Arab Academy for Science, Technology  
& Maritime Transport, Alexandria, Egypt  
Specialization: Experimental Fluid Mechanics  
Egypt.*

**Dr. Minghua Zhou**

*College of Environmental Science and Engineering,  
Nankai University  
Specialization: Environmental Engineering (Water  
Pollution Control Technologies)  
China.*

**Dr. Hossam Hamdy Elewa**

*National Authority for Remote Sensing and Space  
Sciences (NARSS), Cairo, Egypt.  
Specialization: Hydrogeological and Hydrological  
applications of Remote Sensing and GIS Egypt.*

**Dr. Mohamed Mokhtar Mohamed Abdalla**

*Benha University  
Specialization: Surface & Catalysis Egypt.*

**Dr. Michael Horsfall Jnr**

*University of Port Harcourt  
Specialization: (chemistry) chemical speciation and  
adsorption of heavy metals  
Nigeria.*

**Engr. Saheeb Ahmed Kayani**

*Department of Mechanical Engineering,  
College of Electrical and Mechanical Engineering,  
National University of Sciences and Technology,  
Islamabad,  
Pakistan.*

## Editorial Board

### **Prof. Hyo Choi**

*Dept. of Atmospheric Environmental Sciences  
College of Natural Sciences  
Gangneung-Wonju National University Gangneung city,  
Gangwondo 210-702  
Specialization: Numerical forecasting of Rainfall and Flood,  
Daily hydrological forecasting , Regional & Urban climate  
modelling -wind, heat, moisture, water Republic of Korea*

### **Dr. Adelekan, Babajide A.**

*Department of Agricultural Engineering, College of  
Engineering and Technology, Olabisi Onabanjo  
Specialization: Agricultural and Environmental  
Engineering, Water Resources Engineering, Other  
Engineering based Water-related fields.  
Nigeria*

### **Dr. Rais Ahmad**

*Department of Applied Chemistry  
F/O Engineering & Technology  
Aligarh Muslim University  
specialization: Environmental Chemistry  
India*

### **Dr. Venkata Krishna K. Upadhyayula**

*Air Force Research labs, Tyndall AFB, Panama City, FL,  
USA  
Specialization: Environmental Nanotechnology,  
Biomaterials, Pathogen  
Sensors, Nanomaterials for Water Treatment  
Country: USA*

### **Dr. R. Parthiban**

*Sri Venkateswara College of Engineering  
Specialization - Environmental Engineering  
India*

### **Dr. Haolin Tang**

*State Key Laboratory of Advanced Technology for Materials  
Synthesis and Processing, Wuhan University of Technology  
Specialization: Hydrogen energy, Fuel cell China*

### **Dr. Ercument Genc**

*Mustafa Kemal University  
(Aquaculture Department Chairman,  
Faculty of Fisheries,  
Department of Aquaculture, Branch of Fish Diseases,  
Mustafa Kemal University,31200,Iskenderun, Hatay,  
Turkey)  
Specialization: Environmental (heavy metal), nutritional  
and  
hormonal pathologies, Parasitic infections prevalences  
and their histopathologies in aquatic animals  
Turkey*

### **Dr. Weizhe An**

*KLH Engineers, Inc., Pittsburgh, PA, USA.  
Specialization: Stormwater management, urban  
hydrology, watershed modeling, hydrological  
engineering, GIS application in water resources  
engineering.  
USA*

### **Dr. T.M.V. Suryanarayana**

*Water Resources Engineering and Management Institute,  
Faculty of Tech. and Engg.,The Maharaja  
Sayajirao University of Baroda,  
Samiala - 391410, Ta. & Dist.:Baroda.  
Specialization: Water Resources Engineering  
&  
Management, Applications of Soft Computing Techniques  
India*

### **Dr. Hedayat Omidvar**

*National Iranian Gas  
Company Specialization: Gas  
Expert  
Iran*

### **Dr. Ta Yeong Wu**

*School of Engineering Monash University  
Jalan Lagoon Selatan, Bandar Sunway, 46150,  
Selangor Darul Ehsan  
Specialization: Biochemical Engineering;  
Bioprocess Technology; Cleaner Production;  
Environmental Engineering; Membrane  
Technology.  
Malaysia.*

**ARTICLES**

**Risk assessment of cyanobacteria-toxins for small drinking water treatment plants with lake water intakes** 121

Uche A. Uduma, Edward A. McBean and Bahram Gharabaghi

**Irrigation water quality of River Kulfo and its implication in irrigated agriculture, South West Ethiopia** 127

Molla Mekonnen Alemu and Fitsume Yemenu Desta

*Full Length Research Paper*

# Risk assessment of cyanobacteria-toxins for small drinking water treatment plants with lake water intakes

Uche A. Uduma, Edward A. McBean and Bahram Gharabaghi\*

School of Engineering, University of Guelph, Guelph, Ontario N1G 2W1, Canada.

Received 4 July, 2016; Accepted 8 May, 2017

Recent increases in the frequency and severity of toxic algae blooms in freshwater lakes has been a major concern for small communities that rely on them for drinking water supply. A hazard quotient approach to risk characterization is employed to analyze the effectiveness of five conventional treatment methods for removal of cyanotoxins. The application of the method for risk assessment and mitigation is demonstrated for five case studies, including Lake Champlain (Quebec), Coal Lake (Alberta), Butte Lake (Alberta), Kubhani Lake (Nigeria) and Bomo Lake (Nigeria).

**Key words:** Cyanotoxins, human health, hazard quotient, lake water intake, water quality.

## INTRODUCTION

Agricultural non-point source pollution combined with global warming have caused major algal blooms in our freshwater rivers and lakes (Asnaashari et al., 2015; Stang et al., 2016; Gazendam et al., 2016). Cyanobacteria are photosynthetic prokaryotes that thrive well in various kinds of habitats ranging from freshwater and marine environments to hot springs and deserts (Duy et al., 2000; Ballot et al., 2003, 2010; Baxa et al., 2010; Bogialli et al., 2013; Chia et al., 2009, Chia and Kwaghe, 2015). They are popularly referred to as blue-green algae but their physiological, morphological and metabolic structures clearly identify them as bacteria. The photosynthetic origin of cyanobacteria is similar to that of algae but the pigments are located in the thylakoids, which is in the cytoplasm (Chorus et al., 2000; Codd et al., 2005; Drabkova and Marsalek, 2007; Echenique et al., 2014; Ostermaier and Kurmayer, 2010; Sayyad et al., 2015).

One of the basic "metabolic processes of cyanobacteria" is the fixation of di-nitrogen in aerobic conditions using nitrogenase, an enzyme that converts di-nitrogen to ammonium. This process enhances a bloom of cyanobacteria in surface waters (Ernst et al., 2006; Fastner et al., 2007; Fawell et al., 1999; Fischer et al., 2000; Graham et al., 2010; Gilroy et al., 2000; Harvey et al., 2015). Cyanobacteria have many properties which result in their relative success and predominance during the blooming season. The following factors are responsible for cyanobacteria blooms in aquatic habitat: aquatic temperatures above 25°C, low light intensity in water, and low nitrogen-to-phosphorous ratios (Hans and Timothy, 2013; Heisler et al., 2008; Hrudehy et al., 1999; Griffiths and Saker, 2003; Kaushik and Balasubramanian, 2013; Paerl et al., 2011; Tencalla and Dietrich, 1997).

Presently, there about 3000 known species of

\*Corresponding author. E-mail: bgharaba@uoguelph.ca. Tel: 01 (519) 824-4120. Ext: 58451. Fax: 01 (519) 836-0227.

cyanobacteria but not all produce toxins. Due to the increasing numbers of cases of cyanobacteria blooms, the occurrence of several harmful cyano-toxins in water supplies has also increased. There is growing concern about the potential for negative health effects on humans due to these toxins (Keijola et al., 1989; Baker et al., 2015; Makarewicz and Lewis, 2015; Merel et al., 2012; Mohamed et al., 2015).

Notwithstanding the recent scientific and technical advances in drinking water treatment plants around the globe, the concentrations of cyanobacterial-toxins have been reported to increase in treated drinking relative to raw water source for small water treatment plants. These toxins enter water supplies after lysis of cyano-bacterial cells, as induced by water collection and treatment activities resulting in subsequent release of toxins in finished treated waters. The toxins released by blue-green algae cannot be removed by conventional treatment methods (Merel et al., 2010; Newcombe and Nicholson, 2002; Nicholson et al., 2003; Szlag et al., 2015; Westrick et al., 2010; Zamyadi et al., 2012).

Drinking water treatment processes may cause breakthrough of toxins into treated drinking water as demonstrated by Zamyadi et al. (2012) in a full-scale water treatment plant system. The passage of toxins, toxic cells and cell debris through filtration systems inhibited chlorination that resulted in the breakthrough of microcystins, resulting in exceedance of Canadian and WHO water quality standards for treated drinking water. Long-term consumption of water contaminated by cyanobacteria and algae is known to cause liver failure, cardiac arrhythmia, dysfunction of the nervous system and skin tumors (Ontario Health Unit, 2014; Farrer et al., 2015).

The objective of this study is to evaluate the use of conventional treatment options and riverbank filtration for managing cyano-toxins, to assess the vulnerability of existing municipal drinking water facilities using surface water sources.

## STUDY AREAS

The application of the hazard index is demonstrated for five case studies, including Lake Champlain (Quebec), Coal Lake (Alberta), Butte Lake (Alberta), Kubanni Lake (Nigeria) and Bomo Lake (Nigeria).

### Lake Champlain's Missisquoi Bay (Quebec)

The population is about 330,000. The Missisquoi River is 130 km long and a tributary of Lake Champlain. The Missisquoi River cuts across Vermont in the United States and southern Quebec in Canada located between Latitude 45° and 0° E and longitude 72° and 35° due west. The Missisquoi River catchment area covers the Green

mountains along the US-Canada border (Lake Champlain and Eastern townships in Quebec before emptying into Lake Champlain's Missisquoi Bay at Richford (Zamyadi et al., 2012).

### Coal Lake, City of Wetaskiwin (Alberta)

The population is about 12,525. Wetaskiwin is a city in the Province of Alberta Canada (coordinates 52°N and 113°W). Wetaskiwin is located 70 km south of Edmonton; it sits on what was "formerly a coast of the large sea that covered much of Alberta, millions of years ago". Wetaskiwin sits at an elevation of 760 m. Coal Lake, a reservoir developed on the Battle River, is on the east side of the City (Zurawell, 2002).

### Butte Lake, Town of Picture Butte (Alberta)

The population is about 1650. Picture Butte is a city in southern Alberta (coordinates 49° 52' N and 112° 46' W). Picture Butte has a landmass of 2.9 km<sup>2</sup> and sits at an elevation of 900 m, 27 km north of the City of Lethbridge. Old-man River and Picture Butte Lake is the sources of drinking water for this town (Zurawell, 2002).

### Kubanni Lake (Nigeria)

The population of this community is about 560,000. The coordinates of this water body are 11° 08'N and 07° 43'E. It has two major tributaries: Kampagi River and Kubanni River. Kubanni Lake is the major source of water to Ahmadu Bello University community and its environs. Surrounding the Kubanni Lake catchment is agricultural land; the farmers in this location utilize agricultural practices that are not environmentally sustainable for the lake (Chia and Kwaghe, 2015).

### Bomo Lake (Nigeria)

The population is about 300,000. This lake is 6 km north west of ABU Zaria; it is located 11° 12'N and 07° 38'E and about 671 m above sea level (Chia et al., 2009).

## MATERIALS AND METHODS

Due to variations in the species, concentrations and locations of cyanotoxins, appropriate analytical methods are required in order to understand the abundance and occurrence and the potential toxicity of cyanobacterial populations, and to effectively assess the risk of cyanotoxins to humans in drinking water supplies (Kutovaya and Watson, 2014).

Data for small drinking water treatment plants in Eastern Township Quebec, Wetaskiwin Alberta, Picture Butte Alberta, Kubanni and Bomo Lake in Zaira Nigeria are adapted from different

**Table 1.** Concentrations of cyanotoxins in raw and treated water.

Location	Raw water ( $\mu\text{g/L}$ )	Treated water ( $\mu\text{g/L}$ )	References
Eastern Township (Quebec)	118.7	2.47	Zamyadi et al. (2012)
Wetaskiwin (Alberta)	14.8	0.155	Zurawell (2002)
Picture Butte (Alberta)	0.105	0.077	Zurawell (2002)
Kubanni (Nigeria)	3.8	2.8	Chia and Kwaghe (2015)
Bomo (Nigeria)	2.4	1.8	Chia et al. (2009)

**Table 2.** Reference daily doses.

Food	Cyano-toxin	References
Reference daily dose for an adult	0.0001 mg/L	Ohio EPA, 2013
Reference daily dose for a baby	$1.43 \times 10^{-5}$ mg/L	Ohio EPA, 2013

**Table 3.** Hazard quotient summary for an adult and a baby consuming raw water.

Location	Raw water source	Hazard quotient for an adult	Hazard quotient for a baby
Eastern Township	Missisquoi River	33.9	197
Wetaskiwin	Coal Lake	4.2	24.5
Picture Butte	Butte Lake	0.03	0.18
Kubanni	Kubanni Lake	2.17	6.3
Bomo	Bomo Reservoir	1.3	3.9

literature before, and after conventional treatment. Data are collected and monitored on a weekly basis for spring and summer seasons for the raw water samples from these plants; the changing characteristic of the toxins in the raw water and treated drinking water are the major foci for the drinking water data collected.

Table 1 lists the concentrations of cyanotoxins in raw and treated water for the selected study regions. The data in Table 1 are in agreement with the removal efficiencies of Cyanotoxins using the conventional treatment range from 25 to 99%. Apart from Picture Butte in Table 1, the concentrations of cyanotoxins in the raw water for all other locations are above the Canadian guidelines for microcystins in drinking water. Further, the concentrations of cyanotoxins in the treated waters, with the exception of Wetaskiwin and Picture Butte, remained above WHO and Canadian guideline.

### Risk assessment of cyanotoxins

A hazard quotient is the ratio of the potential exposure to a substance and the level at which no adverse effects are expected. Risk assessment using the intake rate, hazard quotient and hazard indices using the equations presented below, are described to determine the risk associated with drinking water contaminated with cyano-bacterial toxins.

$$\text{Intake rate} \left( \frac{\text{mg}}{\text{kg-day}} \right) = \frac{C_w \times IF \times EF \times ED}{BW \times AT} \quad (1)$$

Where: CW = concentration in water (mg/l); IF= intake frequency (L/day); EF = exposure frequency (days); ED = exposure duration (years); BW = body weight (kg); AT = average time (days).

$$\text{Hazard quotient} = \frac{\text{Intake Rate}}{\text{Reference Dose}} \quad (2)$$

Where: HQ = hazard quotient.

The intake rate and hazard quotients for consuming raw water, water after conventional treatment in the two geographical locations are calculated using Equations 1 and 2 using the data presented in Table 2. The calculation conditions below are used in deriving Tables 3 and 4.

### Key assumptions

1. Body weight for adult, 70 kg.
2. Body weight for a baby, 10 kg.
3. Water ingestion rate for an adult is 2 L/day for Canada and 4 L/day for the hot climate in Nigeria.
4. Water ingestion rate for a ten-month-old baby is 0.24 L/day.
5. Unintentional ingestion is 1.5 L/day for Canada and Nigeria.
6. Exposure frequency is 182 days for an adult and a baby in Canada
7. Exposure frequency is 365 days for an adult and a baby in Nigeria
8. The reference dose for an adult is  $0.0001 \frac{\text{mg}}{\text{L}}$  per day for both water (Ohio State Environmental Protection Agency, 2013).
9. Reference dose for a baby is  $\left( \frac{10\text{kg}}{70\text{kg}} \times 0.0001 \right) = 1.43 \times 10^{-5} \frac{\text{mg}}{\text{L}}$  per day.
10. The cyanobacteria toxins in the assumed intake are derived only from water.



**Table 4.** Hazard quotient summary for an adult and a baby consuming treated water.

Location	Raw water source	Water treatment technology	Hazard quotient for an adult	Hazard quotient for a baby
Eastern Township	Missisquoi River	Conventional Treatment (Coagulation, Powdered activated carbon, post clarification and chlorination)	1.6	4.1
Wetaskiwin	Coal Lake	Conventional Treatment (pre-oxidation, clarification and chlorination)	0.04	0.26
Picture Butte	Butte Lake	Conventional treatment, membrane filtration and chlorination	$2.5 \times 10^{-8}$	0.02
Kubanni	Kubanni Lake	Riverbank filtration, sedimentation and chlorination	2.5	4.6
Bomo	Bomo Reservoir	Sand filtration, pre-oxidation and chlorination	1.86	2.9

11. Conventional drinking water treatment plant removal efficiency for cyanobacteria toxins was between 25% for small drinking water treatment plants in Nigeria (Mouchet and Bonnelye, 1998).

## RESULTS

Table 3 summarizes the hazard quotient (the ratio of the potential exposure to a substance and the level at which no adverse effects are expected) of raw water and cow milk for an adult and a baby drinking raw water. From the hazard quotient values presented in Table 3, the results indicate that the Butte Lake is the only safe drinking water in terms of microcystins.

Table 4 presents a summary that relates the hazard index of treated drinking water for an adult and a baby to the water treatment technology used drinking water treatment plants; from the hazard quotient values presented in Table 4, the results indicate that a combination of conventional treatment and membrane filtration which is used in Picture Butte is an efficient technique for removing cyanotoxins.

Table 1 was used together with Equations 1, 2, and 3 to calculate the non-carcinogenic risk for a person that weighs 70 kg and drinks 2 L (Canada) and 4 L (Nigeria) of water daily. The individual drank directly from the contaminated lake. Furthermore, the same approach is performed for a baby that weighs 10 kg and drinks 0.24 L of water per day.

A hazard quotient is the ratio of the potential exposure to a substance and the level at which no adverse effects are expected. The hazard quotients for an adult and a baby consuming raw water are summarized in Table 3. The hazard quotient for an adult consuming raw water in four communities (study areas in Canada and Nigeria) except Picture Butte exceeded unity. This was similar to the hazard quotient for a baby consuming raw untreated water for all the communities under study with the exception of Picture Butte.

The hazard quotients for an adult and a baby consuming treated drinking water is presented in Table 4; for an adult in Eastern Township, Kubanni and Bomo consuming treated drinking water the hazard quotient is

greater than one, while for an adult in Wetaskiwin and Picture Butte consuming treated drinking water, the hazard quotient is less than one. Similarly, the hazard quotient result for a baby consuming treated drinking water in Eastern Township, Kubanni and Bomo exceeds 1, while for a baby consuming treated water in Alberta (Wetaskiwin and Picture Butte), the hazard quotient is less than one.

## DISCUSSION

The presences of cyanotoxins in treated drinking water supply from small water treatment plants reaffirms the need to assess the risk of cyanotoxins from these small water treatment plants. In this study, the hazard quotients for an adult and a baby were calculated for a single exposure of treated water for the five treatment plants. The summary calculations are shown in Table 3. The results indicate that a combination of conventional treatment and membrane filtration used in Picture Butte (Table 4) is an efficient technique for removing cyanotoxins. The other Canadian water treatment plants that use combination of coagulation, activated carbon, oxidation, clarification and chlorination have shown a high percentage of removal of cyanotoxins (greater than 97%). This highlights the importance of adopting a more efficient water treatment technologies in affected areas to minimize the risk to a human receptor. On the other hand, in Nigeria, a simple sand filtration or riverbank filtration combined with only chlorination was found to be ineffective in reducing the cyanotoxins concentration to a safe and tolerable level. The efficiency of cyanotoxins removal for both treatment systems in Nigeria were found to around 25%. The people living in these two communities are exposed to elevated concentration of toxin in their drinking water supply.

The results in the different communities included in this study show clearly that hazard quotient for babies are much higher than that for adults. Excluding Picture Butte community, the increased risk for babies compared to adults is between 1.6 and 4.1 to all other four communities. Moreover, all the results above were

calculated based on a single exposure (drinking water). Therefore, it is expected that the risk index, which is defined as the sum of hazard quotients due to different exposures, is also alarming. Other exposures that were not considered in this study are food crops irrigated with cyanotoxins-contaminated water, inhalation of water aerosols, and other water sports like swimming and surfing (Queensland Health, 2001).

## Conclusions

The assessment of the cyanotoxin removal capacity for small water treatment plants shows that the concentrations of cyanobacterial toxins in treated drinking water in Quebec and northern Nigeria are of concern; the hazard quotient derived from a combination of treated or untreated water from drinking water treatment plants in Quebec and northern Nigeria exceeded unity which indicates the need for appropriate remedial action to be taken or an alternative water supply developed. Also, the intake rate exceeded the recommended World Health Organization intake guideline of 1 µg/L.

Applicable strategies to eliminate cyanobacteria blooms would be appropriate to adopt for water treatment facilities in Eastern Township (Quebec) and northern Nigeria in order to protect consumer's health. A more sustainable strategy that consists of reducing the introduction of nutrients in surface waters is ideal for a long-term solution. Advanced water treatment techniques such as membrane filtration should be adopted since they have been proven to be very effective in treating all kinds of organic contaminants. Small drinking water treatment plants can be upgraded to include membrane filtration and ozonation. This will help to achieve high removal efficiency.

## CONFLICT OF INTERESTS

The authors have not declared any conflict of interests.

## ACKNOWLEDGEMENT

The authors acknowledge the generous support of the National Sciences and Engineering Research Council (NSERC) under Grant number 400675 for their support of this research.

## REFERENCES

- Asnaashari A, Gharabaghi B, McBean E, Mahboubi AA (2015). Reservoir Management Under Predictable Climate Variability and Change. *J. Water Climate Change* 6(3):472-485.
- Baker LC, Manassaram-Baptiste D, LePrell R, Bolton B (2015). Cyanobacterial and algae blooms: Review of health and environmental data from the harmful algal bloom-related illness surveillance system (HABISS) 2007–2011. *Toxins* 7:1048-1064.
- Ballot A, Fastern J, Wiedner C (2010). Paralytic shellfish toxin-producing *Cyanobacterium*. *Alphanizomenon gracile* in Noeast Germany. *Appl. Environ. Microbiol.* 76:1173-180.
- Ballot A, Pflugmacher S, Wiegand C, Kotut K, Krienitz L (2003). Cyanobacterial toxins in Lake Baringo, Kenya. *Limnologica. Tech. Sci. J.* 33:2-9.
- Baxa DV, Kurobe T, Ger KA, Lehman PW (2010). Estimating the abundance of toxic microcystins in San Francisco Estuary using qualitative real-time PCR. *Harmful algae* 9:342-349.
- Bogialli S, Nigro Di Gregorio F, Lucentini L, Ferretti E, Ottaviani M, Ungaro N, Abis PP, Cannarozzi De Grazia M (2013). Management of toxic *Cyanobacterium* bloom (*Planktothrix rubescens*) affecting an Italian drinking water basin: A case study. *Environ. Sci. Technol.* 47:574-583.
- Chia A, Abolude D, Laden Z, Akanbi O, Kalabonus A (2009). The presence of Microcystins in Aquatic ecosystems in Northern Nigeria: Zaria as a Case Study. *Resour. Environ.* 3(4):170-178.
- Chia MA, Kwaghe MJ (2015). Microcystins Microcystins contamination of surface water supply sources in Zaria-Nigeria. *Environ. Monitor. Assess.* 187:10.1007/s10661-015-4829-3.
- Chorus I, Falconer IR, Salas HJ, Bartram J (2000). Health Risks Caused By Freshwater Cyanobacteria In Recreational Waters. *J. Toxicol. Environ. Health Part B* 3:323-347.
- Codd GA, Lindsay J, Young FM Morrison LF, Metcalf JS (2005). Harmful cyanobacteria: from mass mortalities to management measures. Springer: pp. 1-23.
- Drabkova M, Marsalek B (2007). A review of in-lake methods of cyanobacterial blooms control and management. *CyanoData – The Global Database of Methods for Cyanobacterial Blooms Management*, Centre for Cyanobacteria and their Toxins [www.cyanodata.net](http://www.cyanodata.net)
- Duy TN, Lam PKS, Shaw GR, Connell DW (2000). Toxicology and risk assessment of freshwater cyanobacterial (blue-green algal) toxins in water. *Rev. Environ. Contam. Toxicol.* 163:113-186.
- Echenique RO, Aguilera A, Giannuzzi L (2014). Problems on drinking water related to toxigenic *Cyanobacteria*: Some cases studied in Argentina. *Adv. Limnol.* (65):431-444.
- Ernst B, Hoeger SJ, O' Brien E, Dietrich DR (2006). Oral toxicity of the microcystins-containing cyanobacterium *planktothrix rubescens* in European whitefish (*Coregonus lavaretus*). *Aquat. Toxicol.* 79:31-40.
- Farrer D, Counter M, Hillwig R, Cude C (2015). Health-based cyanotoxin guideline values allow for cyanotoxin-based monitoring and efficient public health response to cyanobacterial blooms. *Toxins* 7:457-477.
- Fastner J, Rucker J, Stuken A, Preubel K, Nixdorf B, Chorus I (2007). Occurrence of cyanobacterial toxin cylindrosperosin in northeast Germany. *Environ. Toxicol.* 22:26-32.
- Fawell JK, Mitchell RE, Evertt DJ, Hill RE (1999). The toxicity of Cyanotoxins in the Mouse: microcystins exposure in human. *Exp. Toxicol.* 181:162-167.
- Fischer WJ, Hiltzfield BC, Tencalla F, Eriksson JE, Mikhailov A, Deietrich DR (2000). Microcystin-LR Toxicodynamics, induced pathology and immunohistochemical localization in livers of blue-green algae exposed rainbow trout (*Oncorhynchus mykiss*). *Toxicol. Sci.* 54:365-373.
- Gazendam E, Gharabaghi B, Ackerman J, Whiteley H (2016). Integrative Neural Networks Models for Stream Assessment in Restoration Projects. *J. Hydrol.* 536:339-350.
- Gilroy DJ, Kauffman KW, Hall RA, Huang X, Chu FS (2000). Assessing Potential Health Risk from Microcystin Toxins in Blue-Green Algae Dietary Supplements. *Environ. Health Perspective* 108:435-439.
- Graham J, Loftin K, Meyer M, Ziegler A (2010). Cyanotoxin mixtures and taste and odor compounds in cyanobacterial blooms from Midwest United States. *Environ. Sci. Technol.* 44:7361-7368.
- Griffiths DJ, Saker ML (2003). The Palm Island mystery disease 20 years on: a review of research on the cyanotoxin cylindrospermopsin. *Environ. Toxicol.* 18:78-93.
- Hans WP, Timothy GO (2013). Harmful Cyanobacterial Blooms: Causes, Consequences, and Controls. *Environ. Microbiol.* DOI 10.1007/s00248-012-0159.
- Harvey R, McBean EA, Murphy HM, Gharabaghi B (2015). Using data

- mining to understand Drinking Water Advisories in small water systems: A case study of Ontario First Nations drinking water supplies. *Water Resour. Manage.* 29(14):5129-5139.
- Heisler J, Glibert PM, Burkholder JM, Anderson DM, Cochlan W, Dennison WC, Dortch Q, Gobler CJ, Heil CA, Humphries E, Lewitus A, Magnien R, Marshall HG, Sellner K, Stockwell DA, Stoecker DK, Suddleson M (2008). Eutrophication and harmful algal blooms: a scientific consensus. *Harmful Algae* 8:3-13.
- Hrudey S, Burch MD, Drikas M, Gregory R (1999). Remedial measures. In *Toxic cyanobacteria in water: a guide to their public health consequences, monitoring, and management*. Edited by Chorus I, Bartram JE, Spon FN New York. pp. 275-312.
- Kaushik R, Balasubramanian R (2013). Methods and Approaches for Detection of Cyanotoxins in Environmental samples: A review: *Critical Rev. Environ. Sci. Technol.* 43:1349-1383.
- Keijola A, Himberg K, Esala A, Sivonen K, Kiisvirata L (1989). Removal of cyanobacterial toxins in water treatment processes: laboratory and pilot plant experiments. *Toxic. Assess.* 3:643-656.
- Kutovaya OA, Watson SB (2014). Development and application of a molecular assay to detect and monitor geosmin-producing cyanobacteria and actinomycetes in the Great Lakes. *J. Great Lakes Res.* 40:404-414.
- Makarewicz JC, Lewis TW (2015). Exploring spatial trends and causes in Lake Ontario coastal chemistry: Nutrients and pigments. *J. Great Lakes Res.* 3:794-800.
- Merel S, Clément M, Thomas O (2010). State of the art on Cyanotoxins in water and their behaviour towards chlorine. *Toxicol* 55:677-691.
- Merel S, Walker D, Chicana R, Snyder S, Baures E, Thomas O (2012). State of Knowledge and concerns on Cyanobacterial blooms. *Environ. Int.* 59:303-327.
- Mohamed ZA, Deyab MA, Abou-Dobara MI, El-Sayed AK, El-Raghi WM (2015). Occurrence of cyanobacteria and microcystin toxins in raw and treated waters of the Nile River, Egypt: implication for water treatment and human health. *Environ. Sci. Pollution Res.* 22:11716-11727.
- Mouchet P, Bonnelye V (1998). Solving algae problems: French expertise and worldwide applications. *AQUA* 47(3):125-141.
- Newcombe G, Nicholson BC (2002). Treatment options for the saxitoxin class of Cyanotoxins. *Water Sci. Technol. Water Supply* 2(5-6):271-275.
- Nicholson BC, Shaw GR, Morrall J, Senogles PJ, Woods TA, Papageorgiou J, Kapralos C, Wickramasinghe W, Davis BC, Eaglesham GK, Moore MR (2003). Chlorination for degradation of saxitoxins (paralytic shellfish poisons) in water. *Environ. Technol.* 24(11):1341-1348.
- Ohio State Environmental Protection Agency (2013). *Public Water System Harmful Algal Bloom Response Strategy* 1:1-47.
- Ontario Health Unit (2014). *Beach management guidance document*; Ministry of health and long-term care pp. 1-16.
- Ostermaier V, Kurmayer R (2010). Application of real-time PCR to estimate toxin production by the cyanobacterium *Planktothrix* sp. *Appl. Environ. Microbiol.* 76:3495-3502.
- Paerl HW, Hall NS, Calandrino ES (2011). Controlling harmful cyanobacterial blooms in a world experiencing anthropogenic and climatic-induced change. *Sci. Total Environ.* 409:1739-1745.
- Queensland Health (2001). *Environmental health assessment guidelines: Cyanobacteria in recreational and drinking waters*. Environmental Health Unit Brisbane, Australia.
- Sayyad G, Vassel L, Besalatpour A, Gharabaghi B, Golmohammadi G (2015). Modeling Blue and Green Water Resources Availability in an Iranian Data Scarce Watershed Using SWAT. *J. Water Manage. Modeling* doi: 10.14796/JWMM.C391.
- Stang C, Gharabaghi B, Rudra R, Mahboubi A, Ahmed S (2016). Conservation management practices - success story of the Hog Creek and Sturgeon River Watersheds, Ontario, Canada. *J. Soil Water Conserv.* 71(3):237-248.
- Szlag D, Sinclair J, Southwell B, Westrick J (2015). Cyanobacteria and Cyanotoxins Occurrence and Removal from five High-risk conventional Treatment drinking water plants. *Toxins* 7:2198-2220.
- Tencalla F, Dietrich D (1997). Biochemical Characterization of Microcystin toxicity in trout (*Oncorhynchus mykiss*). *Toxicol* 35:583-595.
- Westrick JA, Szlag DC, Southwell BJ, Sinclair J (2010). A review of cyanobacteria and Cyanotoxins removal /inactivation in drinking water treatment. *Anal. Bioanal. Chem.* 397:1705-1714.
- Zamyadi A, Sherri L, Yan F, McQuaid N, Dorner S, Sauve S, Prevost M (2012). Toxic cyanobacterial breakthrough and accumulation in a drinking water treatment plant: A monitoring and treatment Challenge. *Water Res.* 46:1511-1523.
- Zurawell R (2002). An initial Assessment of Microcystin in Raw and Treated Municipal drinking water derived from Eutrophic surface waters in Alberta. 1-15: <http://environment.gov.ab.ca/info/library/6026.pdf>

*Full Length Research Paper*

# Irrigation water quality of River Kulfo and its implication in irrigated agriculture, South West Ethiopia

Molla Mekonnen Alemu<sup>1\*</sup> and Fitsume Yemenu Desta<sup>2</sup>

<sup>1</sup>De Montfort University, Leicester City, England.

<sup>2</sup>School of Environmental and Rural Sciences, University of New England, 2351, Armidale, Australia.

Received 24 November; 2016; Accepted 8 May, 2017

Irrigation is a common agricultural practice for farmers in the periphery of flowing rivers in Ethiopia. In the south west Ethiopia, fruits and vegetables are majorly produced under irrigation where the mode of irrigation is by pumping water from flowing rivers. Irrigated agriculture has only been linked to the availability of water in physical terms, while the quality of water is significantly important for sustainable agricultural production. A study was conducted to assess the water quality parameter of the Kulfo River in South West part of Ethiopia. Accordingly, the concentration of calcium cation (21 g/L) is the highest concentrated followed by sodium (8.3 g/L), magnesium (5 g/L) and potassium (1.8 g/L) is the least concentrated in the Kulfo River. The concentration level of the chloride ion has significantly (25 mg/L) increased from what it was reported (3 to 12 mg/L) in 2004. More importantly, both the electrical conductivity and the sodium adsorption ratio are relatively low, implicating the water is non saline and can safely be used for irrigation.

**Key words:** Electrical conductivity, irrigation water, pumping, sodium absorption ratio, river.

## INTRODUCTION

Irrigation practices have played an important role in increasing agricultural production and productivity so as to meet the ever increasing food, fibre, etc. demands of the growing population. Water resources like rivers and streams are serving as source of irrigation water, while crossing different territories. Irrigated agriculture, however, has only been linked to the availability of water in physical terms while the quality of water is significantly important for sustainable agricultural production. However, the latter has often been neglected, until the situation when most of irrigated agriculture is heavily

dependent on lower water quality and less desirable sources elsewhere in the world (FAO, 1985; Islam et al., 2004). Water quality concerns have often been neglected because good quality water supplies have been plentiful and readily available (Islam et al., 2004; Causapé et al., 2004; Rao and Devadas, 2005; Raju, 2006; Singh et al., 2008; Dhirendra et al., 2009; Megersa et al., 2009).

Salinity is a common problem facing farmers who irrigate in arid climates. This is because all irrigation waters contain soluble salts. Whether derived from springs, diverted from streams, or pumped from wells, the

\*Corresponding author. E-mail: [mollamekonnen@gmail.com](mailto:mollamekonnen@gmail.com).

waters contain appreciable quantities of chemical substances in solution, dissolved from the geological strata through and over which the waters have flowed. Waters with a high salt content may have moved from a saline water table. In areas with intensive agriculture, fertilization is a major cause of aquifer salinization. The composition of salts in water varies according to the source and properties of the constituent chemical compounds (Guy, unpublished).

These salts include substances such as gypsum (calcium sulphate,  $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ ), table salt (sodium chloride  $\text{NaCl}$ ) and baking soda (sodium bicarbonate  $\text{NaHCO}_3$ ). When dissolved in water, salts separate into ions; e.g. sodium chloride breaks down into sodium and chloride ions. Thus, it is customary to refer to ions rather than salts under low quality water, the performance of irrigated agriculture is expected to be below normal, in addition to its environmental impact on soil system. The application of irrigation water to the soil introduces salts into the root zone. Plant roots take in water but absorb very little salt from the soil solution. Similarly, water evaporates from the soil surface but salts remain behind. Both processes result in the gradual accumulation of salts in the root zone, even with low salinity water. This situation may affect the plants in two ways: (a) by creating salinity hazards and water deficiency; and (b) causing toxicity and other problems (Singh et al., 2008; Sukhdev, 2012).

The build-up of salinity in the root zone increases the osmotic pressure of the soil solution and causes a reduction in both the rate of water absorption by the plants and the soil water availability. Thus, a continuous water deficiency may exist even though the field is heavily irrigated. Plant wilting symptoms may not become apparent, but growth and yield are depressed. Under such circumstances, it is not possible to maintain good crop growth and development conditions and obtain high yields. Instead, plant growth is delayed and there will be a considerable reduction in yield. Seed germination is also affected by the presence of salts. It is usually delayed and in some cases does not occur. The level of salinity build-up depends on both the concentration and the composition of salts in the water. Chloride is highly soluble and remains in the soil solution, while sulphate and bicarbonate combine with calcium and magnesium, where present, to form calcium sulphate and calcium carbonate, which are sparingly soluble compounds (Quddus and Zaman, 1996).

The use of such saline water with excessive salt content may also cause secondary salinization of cultivated soils, and bring a series of serious consequences to the agricultural environment and the ecosystem (Kumar et al., 2015). The use of saline irrigation directly affects the soil profile and the dissolved salts may cause changes in the salt balance of the soil system. Zhai et al. (2015) reported that the salt concentration in the soil profile under tomato production


was increased by 47% for the use of saline water more than 5 dS/m.

The chemical constituents of irrigation water can affect plant growth directly through toxicity or deficiency, or indirectly by altering availability of nutrients (Ayers and Westcot, 1985). For instance, in the study conducted in China, it was confirmed that irrigation water more than 5 Ds/m significantly affect the fruit yield of tomato (Zhai et al., 2015). The associated effect of salt in irrigation is attributed to decreased turgor pressure, a lowered speed of cell expansion and damage to chloroplasts, thus reducing the growth rate and photosynthesis. These changes ultimately influence the dry matter accumulation and yield of crops. Ragab (2004) also substantiated that there was a progressive increase in the soil salinity as saline water is continuously used for irrigation. The source of water is the most important phenomenon, whether it is a canal or drainage water. Drainage water is usually affecting the soil system than the water from the canal, in terms of salinity. The complicated nature of the interaction of soils systems and water is governed by the process the exchange of chemical between the water and the soil (Asante et al., 2005).

The other most important problem of the effect of the poor quality water is toxicity of some ions in irrigation water. Many fruit trees and other cultivations are susceptible to injury from salt toxicity. Chloride, sodium and boron are absorbed by the roots and transported to the leaves where they accumulate. In harmful amounts, they result in leaf burn and leaf necrosis. Moreover, direct contact during sprinkling of water drops with a high chloride content may cause leaf burn in high evaporation conditions. To some extent, bicarbonate is also toxic. Other symptoms of toxicity include premature leaf drop, reduced growth and reduced yield. In most cases, plants do not show clear toxicity problems until it is too late to remedy the situation.

Chloride and sodium ions are both present in the solution. Thus, it is difficult to determine whether the damage caused is due to one or to the other. Chloride ions in high concentrations are known to be harmful to citrus and many woody and leafy field crops. A chloride content exceeding 10 meq/litter may cause severe problems to crops. The effect of sodium toxicity is not very clear. However, it has been found that it may cause some direct or indirect damages to many plants. Boron is an essential element to the plants. However, where present in excessive amounts, it is extremely toxic, even at relatively very low concentrations of 0.6 mg/litter. Toxicity occurs with the uptake of boron from the soil solution. The boron tends to accumulate in the leaves until it becomes toxic to the leaf tissue and results in the death of the plant. In arid regions, boron is considered the most harmful element in irrigation water (Guy, unpublished).

In assessing, the quality of irrigation water, one has to identify the relative concentration of the cations, ions and compounds that have a direct effect on plant physiology,



**Figure 1.** Location map of the study area.

growth and also the soil system. More importantly, the acceptable limits of the concentrations should be known. There are a number of laboratory techniques to measure the quality of water for each of the parameters. For instance, the suitability of water for irrigation is usually assessed by measuring the total dissolved salts (TDS) and or the electrical conductivity where a close relationship exists between the two measurements. But the latter is easier and TDS is easily inferred from the electrical conductivity. The acidity or alkalinity of water is assessed by pH reading where the hydrogen ion concentration of water is directly measured in the water solution.

Given that water is available for irrigation practice, proper assessment and analysis of the quality of water is congruently importance. Information on the quality of water will support to develop strategies for appropriate irrigation practices that will reduce the impact of the undesirable chemicals on proposed crop yields and also the soil profile. In Ethiopia, particularly, at Kulfo River where this study has been conducted, data on water quality of rivers is scarcer, and the purpose of this study was therefore to make the information available so that it can assist future irrigation water management options.

## MATERIALS AND METHODS

The study site is located Arba Minch Zuriya district in the Gamo Gofa zone of the Southern Nations and Nationalities Peoples' Regional State of Ethiopia. Situated in the Great Rift Valley region, the district is located about 505 km south west of Addis Ababa, the capital of the country. The district has a total of 29 kebeles (the smallest administration unit in the country). Agro ecologically 4 kebeles are highlands, 15 kebeles at mid altitude and the rest 10 are found in the low land zone. The district has a total area of 168,172 hectares and the total population is 74,879 in Arba Minch city (the capital of the Zone and the district) and 164,529 in Arba Minch Zuriya district. The altitude of the district ranges from 1200 - 3300 masl with a rainfall amount of 800 to 1200 mm per annum. The temperature also ranges from 16 - 37°C. There are two cropping seasons, namely, Belg (short rainy season from March to May), Meher (main rainy season of June to September). The district is also surrounded by the two Rift Valley lakes namely Chamo and Abaya that have a great economic as well as ecological value to the area (FDRE-PCC, 2008).

The district has about 8 major rivers of which River Kulfo is being used by farmers and private investors to grow different crops. The smallholder farmers and the private investors grow crops like banana, mango, papaya, maize, cotton, sweet potato, etc. (Zenebe et al., 2015) (Figure 1).

The upper catchment of the Kulfo River where samples were taken is presented in Figure 2. The widely accepted threshold values for classifying the suitability of water for irrigation (FAO,





**Figure 2.** The upper catchment of where water samples was taken

**Table 1.** Quality parameters and procedures and equipment.

Quality parameters	Equipment
pH	pH meter reading
Electrical conductivity	EC meter reading
Chloride	Argentometric titration with silver nitrate method
Nitrate	DR_2800 spectrophotometric
Calcium	EDTA titrimetric method
Soluble reactive phosphorous (SRP)	Spectrophotometry
Potassium	
Turbidity	The nephelometric turbidimetric
Total dissolved salts	Weighing
Total Hardness as $\text{CaCO}_3^{-2}$	

1989) were used. The analysis for the physio-chemical parameters of the samples was carried out using the standard laboratory procedures. Electrical conductivity (ECw) and pH ( $\text{H}_2\text{O}$ ) were determined using electrical conductivity meter provided with automatic temperature compensation and potentiometrically with pH-meter equipped with single probe combined glass-calomel electrode (Greenbergs et al., 1992) respectively. Soluble  $\text{Na}^+$  and  $\text{K}^+$  were determined by flame-photometer after proper calibration with combined Na-K standard solutions (RTI, 1991), while soluble  $\text{Ca}^{+2}$  and  $\text{Mg}^{+2}$ , were analyzed directly by atomic absorption spectrophotometer (APHA, 1998). Chloride ( $\text{Cl}^-$ ) and  $\text{HCO}_3^-$  ions were measured by the argentometric method, by titrating against silver nitrate standard solution with potassium chromate indicator with a procedure from (Greenbergs et al., 1992). The turbid metrical procedures were solid residues weighed after evaporation for measuring TDS (Chopra and Kanwar, 1980). Similarly, sulfate ( $\text{SO}_4^{2-}$ ) was analyzed turbidmetrically as described by Rezwani et al. (2007) and nitrate content ( $\text{NO}_3^-$ ) was determined with spectrophotometric (AOAC, 1990).

The water quality parameters tested and the procedures and equipment used is described in Table 1.

## RESULTS AND DISCUSSION

The concentration of important cations of the irrigation water is presented as in Table 1. Calcium cation (21 g/L) had the highest concentrated followed by sodium (8.3 g/L), magnesium (5) and potassium (1.8) has the least concentrated in the Kuflo River. The relatively higher concentration of the calcium cations can be linked with the existence of the calcium bicarbonate in the river (Ababu and Bern, 2014) which might have originated from basaltic formation of parent rock in the region. The relatively high concentration of calcium cation may limit the hazardous effect of sodium which latter causes the dispersion of the soil aggregates and eventually creating problem water and movement in the soil systems (Mathess, 1982). The low level of potassium concentration in the water may implicate minimum wash away of the fertilizers from the soil into the water from the

**Table 2.** Concentration of cations in the river.

Cations	Concentration (mg/L)
Sodium ( $\text{Na}^{+1}$ )	8.3
Potassium ( $\text{K}^{+1}$ )	1.8
Calcium( $\text{Ca}^{+2}$ )	21
Magnesium ( $\text{Mg}^{+2}$ )	5

**Table 3.** Anion concentration in the river.

Anions	Concentration (mg/L)
Sulfate as $\text{SO}_4^{-2}$	14
Nitrate as $\text{NO}_3^{-1}$	34
Nitrite as $\text{NO}_2^{-1}$	0.38
Boron	0.01
Phosphate as $\text{PO}_4^{+3}$	0.24
Carbonate as $\text{CaCO}_3^{-2}$	0
Bicarbonate as $\text{CaHCO}_3^{-1}$	145
Chloride as $\text{Cl}^{-1}$	25

upstream farming areas. However, this could be relatively higher in the downstream areas where compounds may settle (Table 2).

Similarly, the ion concentrations of the important anions for the quality of water are presented in Table 3. The bicarbonate ion is highly concentrated followed by the chlorides and nitrates. The abundant presence of the bicarbonate is again associated with the basaltic formation of the parent material in the vicinity areas of the river, Kulfo. The relatively high nitrates in the form of  $\text{NO}_3$  could be associated with high use of nitrogen fertilizers and agrochemicals in the upstream areas. Furthermore, the relative high concentration of nitrates in this form might have been linked to the repeated irrigation practices in the area.

The concentration level of the chloride ion has significantly (25 mg/L) increased from what it was reported (3 to 12 mg/L) in 2004 by Ababu and Bern (2004). The chloride ion can be taken up by plant roots and accumulate in the leaves. The progressive increase of the chloride ion is a warning that there could be some sorts of pollution to the water due to human activity, though the current range is no hazardous. Excessive accumulation of chloride may cause burning of the leaf tops or margins, bronzing and permanent yellowing. Most importantly, fruit trees are sensitive while there are moderate, crops, like vegetables. In general, intents of the nature of the concentration of ions and anions, the water is still safe for irrigating for most of the crops.

The most important water quality parameters are presented in Table 3. Accordingly, both the electrical conductivity and the sodium adsorption ration are

**Table 4.** Irrigation water quality parameters.

Parameter	Unit	Values
Total dissolved salts	mg/L	87
Turbidity	NTU	68
Sodium abortion ratio (SAR)	meq/L	0.593
Electrical conductivity (EC)	$\mu\text{S}/\text{cm}$	99
pH	Unit	8.1
Total alkalinity	mg/L	145
Na %	%	35.5

relatively low and it implicates that the water is non saline and can safely be used for irrigation. The electrical conductivity of water is an important quality parameter that categorizes the nature of water for irrigation use. Irrigation water with more than 0.7 dS/m and TDS greater than 450 mg/l are labelled as saline water and caution need to be taken in using the water. The high electrical conductivity of water affects the water availability to plants once it enters the soil profile and eventually reduces the growth and yield of crops. For instance, under repeated irrigation, salinity levels of a saline water with greater than 3 dS/m would reduce the total yield of lemon and keeping the salinity of irrigation water is critical for areas that are irrigated continuously (Blaine et al., 2006).

In the due courses of climate change that causes more evaporative demand and repeated irrigation practices, the development of soil salinity is expected. Due to the complicated interaction of the soil system and water bodies, the rise in the salt concentration of water is axiomatic. Kulfo River is located in the semi-arid areas of Ethiopia, the contribution of climate change and interest in the expansion of irrigation would impact the chemical composition of the water. Hence, proper use of irrigation water demands protection of the river from polluting substances from the upper catchment that may be engaged in irrigated agriculture (Table 4).

As expected, the alkalinity (145 mg/l) of the water is relatively high and corresponds to the high concentration of the bicarbonates in the water. The turbidity of water is high and might have resulted from anthropogenic activities in the vicinity of the river. Among which, construction and agricultural production trend might have disturbed land surfaces, potentially contributing to soil particles as well as nutrients to aquatic systems. Landscape fertilization and chemicals for weed control activities tend to be leached into the river.

## Conclusions

Irrigation is a common practice for farmers in the periphery of flowing rivers in Ethiopia. In the south west Ethiopia, fruits and vegetables are majorly produced



under irrigation where the mode of irrigation is by pumping water from flowing rivers. Irrigated agriculture has only been linked to the availability of water in physical terms while the quality of water is significantly important for sustainable agricultural production. A study was conducted to assess the water quality parameter of the Kuflo River in South West part of Ethiopia. Accordingly, the analysis of the results showed that calcium cations is the highest concentration followed by sodium, magnesium and potassium is the least concentrated in the Kuflo River. The relatively higher concentration of the calcium cations can be linked to the existence of the calcium bicarbonate in the river which might have originated from basaltic formation of parent rock in the region. Similarly, the bicarbonate ion is the highest concentrated followed by the chlorides, and nitrates. The abundant presence of the bicarbonate is again associated with the basaltic formation of the parent in the vicinity areas of the river, Kuflo. The relatively high nitrates in the form  $\text{NO}_3$  could be associated with high use of nitrogen fertilizers and agrochemicals in the upstream areas. Furthermore, the relative high concentration of nitrates in this form might have been linked to the repeated irrigation practice in the area. More importantly, both electrical conductivity and sodium adsorption ratio are relatively low and it implicates that water is non-saline and can safely be used for irrigation.

## CONFLICT OF INTERESTS

The authors have not declared any conflict of interests.

## REFERENCES

- Ababu T, Bern E (2004). Water Quality of Monitoring the Abaya-Chamo Drainage Basin. FWU VOL. 4, Lake Abaya Research Symposium 2004 proceedings.
- AOAC (1990). Official Methods of Analysis of the Association Analytical chemists. 15th ed. Virginia, USA.
- APHA (American Public Health Association) (1998). Standard Methods for the Examination of Water and Waste Water'. 17th ed. Washington, D.C. 200005. pp. 1-30 to 40-175.
- Asante K, Quarcoopome T, Amevenku F (2005). Water Quality of the Weija Reservoir after 28 years of Impoundment. *West Afr. J. Appl. Ecol.* 13:171-180.
- Ayers RS, Westcot DW (1985). Water Quality for Agriculture, Irrigation and Drainage Paper 29, rev. 1, FAO, United Nations, Rome.
- Blaine RH, Stephen RG, Allan F (2006). Agricultural Salinity and Drainage. Division of Agriculture and Natural Resources Publication 3375, University of California Irrigation Program, University of California, Davis.
- Causapé J, Quílez D, Aragües R (2004). Assessment of irrigation and environmental quality at the hydrological basin level irrigation quality. *Agric. Water Manage.* 70:195-209.
- Chopra SL, Kanwar JS (1980). Analytical Agricultural Chemistry', Kalyan Publishers, New Delhi. pp. 168-307.
- Dhirendra M, Alok K, Namita A (2009). Assessment of the irrigation water quality of river Ganga in Haridwar district. *Rasāyan J. Chem.* 2(2):285-292.
- FAO (Food and Agriculture Organization) (1985). Water quality for agriculture. FAO Irrigation and Drainage Paper No. 29 (Rev. 1). Rome. Italy. pp. 1-140.
- FAO (1989). Water quality for agriculture. FAO, Rome, P 163.
- FDRE-PCC (Federal Democratic Republic of Ethiopia, Population Census Commission) (2008). Summary and Statistical Report of the 2007 Population and Housing Census. Addis Ababa, Ethiopia.
- Guy (undated). Irrigation Water Quality Standards and Salinity Management, the Texas A and M university, access date 24 -11-2016 <http://soiltesting.tamu.edu/publications/B-1667.pdf>
- Greenberg AE, Clesceri LS, Eaton AD (1992). Standard Methods for the Examination of Water and Waste water (18thEd.). American Public Health Association, American Water Works Association, Water Pollution Control Federation, Washington DC.
- Islam MR, Jahiruddin M, Islam S (2004). Assessment of Arsenic in the water-soil-plant systems in Gangetic Floodplains of Bangladesh'. *Asian J. Plant Sci.* 3(4):489-493.
- Islam MS, Shamsad SZKM (2009). Assessment of Irrigation Water Quality of Bogra District in Bangladesh. *Bangladesh J. Agric. Res.* 34(4):597-608.
- Mathess G (1982). The Properties of Groundwater. John Wiley and Sons, New York. P 406.
- Megersa O, Willibald L, Josef F (2009). Effect of Lake Basaka expansion on the sustainability of Metahara SE in the Awash River basin, Ethiopia. Water, sanitation and hygiene: sustainable development and multi sectoral approaches. 34th WEDC International Conference, Addis Ababa, Ethiopia.
- Quddus KG, Zaman MW (1996). Irrigation water quality in some selected villages of Meherpur in Bangladesh. *Bangladesh J. Agric. Sci.* 23(1):51-57.
- Ragab AM (2004). Influence of irrigation with saline drainage waters on some soil physico-chemical properties of the northern west area of Nile delta. *Fayom J. Agric. Res. Dev.* 18(1):133-142.
- Raju NJ (2006). Hydrogeo chemical parameters for assessment of groundwater quality in the upper Gunjanaeru River basin, Cuddapah District, Andhra Pradesh, India. *Environ. Geol.* 52(6):1067-1074.
- Rao NS, Devadas DJ (2005). Quality criteria for ground water use for development on an area. *J. Appl. Geochem.* 7(9):145-160.
- Rezwanul M, Naoto I, Ranjit S (2007). Assessment of Irrigation Water Quality by Using Principal Component Analysis in Arsenic Affected Area of Bangladesh. *J. Soil Nature* 1(2):08-17.
- RTI (Royal Tropical Institute) (1991). Analytical Methods of the Laboratory for Soil, Plant and Water Analysis. Part I: Methods for Soil Analysis. Amsterdam, the Netherlands.
- Singh AK, Mondal GC, Suresh Kumar TB, Singh BK, Tewary A (2008). Major ion chemistry, weathering processes and water quality assessment in upper catchment of Damodar River basin, India. *Environ. Geol.* 54:745-758.
- Sukhdev K (2012). Assessment of Surface Water Quality for Drinking and Irrigation Purposes: A Case Study of Ghaggar River System Surface Waters. *Bull. Environ. Pharmacol. Life Sci.* 1(2):1-6.
- Zenebe W, Ali M, Derbew B, Zekarias S, Adam B (2015). Assessment of Banana Production and Marketing in Ethiopia. *Int. J. Sci. Basic Appl. Res.* 24(3):283-307.
- Zhai Y, Yang Q, Hou M (2015). The Effects of Saline Water Drip Irrigation on Tomato Yield, Quality, and Blossom-End Rot Incidence - -- A 3a Case Study in the South of China. *PLoS ONE* 10(11): e0142204. <https://doi.org/10.1371/journal.pone.0142204>.



# International Journal of Water Resources and Environmental Engineering

## Related Journals Published by Academic Journals

- *International Journal of Computer Engineering Research*
- *Journal of Chemical Engineering and Materials Science*
- *Journal of Civil Engineering and Construction Technology*
- *Journal of Electrical and Electronics Engineering Research*
- *Journal of Engineering and Computer Innovations*
- *Journal of Engineering and Technology Research*
- *Journal of Mechanical Engineering Research*
- *Journal of Petroleum and Gas Engineering*

**academicJournals**