

15 March 2019 ISSN 1992-2248 DOI: 10.5897/SRE www.academicjournals.org



About SRE

Scientific Research and Essays (SRE) is a peer reviewed open access journal with the objective of publishing quality research articles in science, medicine, agriculture and engineering such as Nanotechnology, Climate Change and Global Warming, Air Pollution Management and Electronics etc.

SRE has an h5-index of 12 on Google Scholar Metrics

Indexing

Scientific Research and Essays is indexed in: Abstracts on Hygiene and Communicable Diseases

AgBiotech News and Information, Agricultural Engineering Abstracts, Agroforestry Abstracts, Animal Breeding Abstracts, Animal Production Database, Biocontrol News and Information Biofuels Abstracts, Botanical Pesticides, CAB Abstracts, CABI's Environmental Impact Chemical Abstracts (CAS Source Index), Crop Physiology Abstracts, Crop Science Database Dairy Science Abstracts, Field Crop Abstracts, Forest Products Abstracts Forest Science Database, Forestry Abstracts, Google Scholar, Grasslands and Forage Abstracts Helminthological Abstracts, Horticultural Science Abstracts, Irrigation and Drainage Abstracts Leisure, Recreation and Tourism Abstracts, Maize Abstracts, Matrix of Information for The Analysis of Journals (MIAR), Microsoft Academic, Nematological Abstracts.

Open Access Policy

Open Access is a publication model that enables the dissemination of research articles to the global community without restriction through the internet. All articles published under open access can be accessed by anyone with internet connection.

The Scientific Research and Essays is an Open Access journal. Abstracts and full texts of all articles published in this journal are freely accessible to everyone immediately after publication without any form of restriction.

Article License

All articles published by Scientific Research and Essays are licensed under the Creative Commons Attribution 4.0 International License. This permits anyone to copy, redistribute, remix, transmit and adapt the work provided the original work and source is appropriately cited. Citation should include the article DOI. The article license is displayed on the abstract page the following statement:

This article is published under the terms of the Creative Commons Attribution License 4.0 Please refer to https://creativecommons.org/licenses/by/4.0/legalcode for details about Creative Commons Attribution License 4.0

Article Copyright

When an article is published by in the Scientific Research and Essays, the author(s) of the article retain the copyright of article. Author(s) may republish the article as part of a book or other materials. When reusing a published article, author(s) should;

Cite the original source of the publication when reusing the article. i.e. cite that the article was originally published in the Scientific Research and Essays. Include the article DOI

Accept that the article remains published by the Scientific Research and Essays (except in occasion of a retraction of the article)

The article is licensed under the Creative Commons Attribution 4.0 International License.

A copyright statement is stated in the abstract page of each article. The following statement is an example of a copyright statement on an abstract page.

Copyright ©2016 Author(s) retains the copyright of this article.

Self-Archiving Policy

The Scientific Research and Essays is a RoMEO green journal. This permits authors to archive any version of their article they find most suitable, including the published version on their institutional repository and any other suitable website.

Please see http://www.sherpa.ac.uk/romeo/search.php?issn=1684-5315

Digital Archiving Policy

The Scientific Research and Essays is committed to the long-term preservation of its content. All articles published by the journal are preserved by <u>Portico</u>. In addition, the journal encourages authors to archive the published version of their articles on their institutional repositories and as well as other appropriate websites. <u>https://www.portico.org/publishers/ajournals/</u>

Metadata Harvesting

The Scientific Research and Essays encourages metadata harvesting of all its content. The journal fully supports and implement the OAI version 2.0, which comes in a standard XML format. See Harvesting Parameter

Memberships and Standards



Academic Journals strongly supports the Open Access initiative. Abstracts and full texts of all articles published by Academic Journals are freely accessible to everyone immediately after publication.

© creative commons

All articles published by Academic Journals are licensed under the Creative Commons Attribution 4.0 International License (CC BY 4.0). This permits anyone to copy, redistribute, remix, transmit and adapt the work provided the original work and source is appropriately cited.



Crossref is an association of scholarly publishers that developed Digital Object Identification (DOI) system for the unique identification published materials. Academic Journals is a member of Crossref and uses the DOI system. All articles published by Academic Journals are issued DOI.

Similarity Check powered by iThenticate is an initiative started by CrossRef to help its members actively engage in efforts to prevent scholarly and professional plagiarism. Academic Journals is a member of Similarity Check.

CrossRef Cited-by Linking (formerly Forward Linking) is a service that allows you to discover how your publications are being cited and to incorporate that information into your online publication platform. Academic Journals is a member of CrossRef Cited-by.



Academic Journals is a member of the International Digital Publishing Forum (IDPF). The IDPF is the global trade and standards organization dedicated to the development and promotion of electronic publishing and content consumption.



<u>COUNTER</u> (Counting Online Usage of Networked Electronic Resources) is an international initiative serving librarians, publishers and intermediaries by setting standards that facilitate the recording and reporting of online usage statistics in a consistent, credible and compatible way. Academic Journals is a member of <u>COUNTER</u>



Portico is a digital preservation service provided by ITHAKA, a not-for-profit organization with a mission to help the academic community use digital technologies to preserve the scholarly record and to advance research and teaching in sustainable ways.

Academic Journals is committed to the long-term preservation of its content and uses Portico



Academic Journals provides an <u>OAI-PMH</u>(Open Archives Initiatives Protocol for Metadata Harvesting) interface for metadata harvesting.

Contact

Editorial Office:	sre@academicjournals.org
Help Desk:	helpdesk@academicjournals.org
Website:	http://www.academicjournals.org/journal/SRE
Submit manuscript online	http://ms.academicjournals.org

Academic Journals 73023 Victoria Island, Lagos, Nigeria ICEA Building, 17th Floor, Kenyatta Avenue, Nairobi, Kenya.

Editor-In-Chief

Prof. N.J. Tonukari Department of Biochemistry Delta State University Abraka, Nigeria.

Editors

Dr. Vishnu Narayan Mishra

Department of Applied Mathematics and Humanities (AMHD), Sardar Vallabhbhai National Institute of Technology, Surat, India.

Dr. Gökçen Firdevs Yücel Caymaz Industrial Product Design, Istanbul Aydin Univeristy, Turkey.

Dr. Junning Li School of Mechatronic Engineering Xi'an Technological University, China

Prof. Luigi Maxmilian Caligiuri

University of Calabria and Foundation of Physics Research Center (FoPRC), ITALY

Dr. Tolga Gok Torbali Technical Vocational School of Higher Education, Dokuz Eylul University, Turkey

Dr. Jiawang Zhou Department of Chemistry, Northwestern University, USA **Dr. Neelaabh Shankar** Biopharma, Finnegan, Henderson, Farabow, Garrett and Dunner LLP,USA.

Dr. Hussein Togun Department of Mechanical Engineering, University of Thiqar, Iraq

Dr. Kamal Salih Taha Electrical and Computer Engineering, Khalifa University, United Arab Emirates

Dr. Sang-Bing Tsai Zhongshan Institute, University of Electronic Science and Technology of China, China

Dr. Vembu Ananthaswamy Department of Mathematics, The Madura College (Autonomous), Madurai, Tamil Nadu, India

Table of Content

Precision attributes based index for the selection of efficient agricultural machinery Manjeet Singh, Karun Sharma, Pramod Mishra, Bharat Patel1 and S K Singh 24



Full Length Research Paper

Precision attributes based index for the selection of efficient agricultural machinery

Manjeet Singh¹, Karun Sharma^{2*}, Pramod Mishra¹, Bharat Patel¹ and S K Singh¹

¹Department of Farm Machinery and Power Engineering, Punjab Agricultural University, Ludhiana, India. ²Krishi Vigyan Kendra, Samrala, Punjab Agricultural University, Ludhiana, India.

Received 5 May, 2016; Accepted 25 January, 2017

Development and introduction of high capacity, precise, reliable and energy efficient machinery/equipment is the need for judicious use of inputs. Manufacturing of agricultural machinery in India is varied in nature and starts from village artisans, tiny units, cottage to small scale industries, organized tractor and agricultural machinery manufacturers including energy and processing machinery industry. Precision in application rates for higher input-use efficiency can be achieved only by improving the designs of the existing machinery/equipment. Precision index (PI) of machine/equipment is based on its capability to perform a given task in an accurate manner. It is a worthwhile attribute to compare the performance of different equipment and operations to enhance the productivity of a given farm. The purpose of study was to propose an index, that is, PI to select efficient and precise machine/equipment for the farmers. PI values were calculated for three types of machinery namely zero seed cum fertilizer drills, planters and spraying machines. It was concluded that drill Make 2, tested in the year 2004, was having the highest PI value, that is, 0.97 or 97% followed by drill Make 1 having PI value 0.95 or 95% tested in the same year. Drill Make 5 tested in the year 2013 was having minimum PI value, that is, 0.80 or 80%. PI value for happy seeder machine was 0.88 or 88%. During the testing of multi-crop planter in year 2014, the variability of doubling attribute was more, that is, 28% followed by missing having 20% value and produced influence on PI which was observed to be 0.83 or 83%. Pl of semi-automatic and automatic potato planter was found to be 0.70 and 0.80, respectively. The value was not much satisfactory and could be ranked under average category. Pl of electrostatic sprayer mounted with single as well as twin nozzle was observed to be the highest, that is, 0.89 followed by PI of air assisted sprayer with single and double nozzle, that is, 0.83 and 0.84, respectively.

Key words: Precision index, zero till seed cum fertilizer drill, happy seeder, spraying machines, planting machines.

INTRODUCTION

Mechanization imparts capacity to the farmers to carry out farm operations, with ease and lesser drudgery. It helps the farmers to achieve timeliness, precisely meter and apply costly input with better efficacy and efficiency. Efficient machinery helps in increasing productivity by about 30% (Kulkarni, 2012) besides enabling the farmers

*Corresponding author. E-mail: karunluckysharma@gmail.com.

Author(s) agree that this article remain permanently open access under the terms of the <u>Creative Commons Attribution</u> <u>License 4.0 International License</u> to raise second crop in a year. Raising more crops with high productivity is a path for meeting the future food requirement of population. Development and introduction of high capacity, precise, reliable and energy efficient equipment is the need for judicious use of inputs. For crop production human, animal and mechanical energy is extensively used. There is increase in crop productivity up to 12 to 34% due to mechanization along with enhancement in cropping intensity by 5 to 22%. Seedcum-fertilizer drill facilitates saving in seeds and fertilizer about 20%. There is an increase in the gross income of the farmers in the range of 29 to 49% due to mechanisation (Anonymous, 2013). Zero till drill was found to be most time saving (88%) and energy efficient (79%) as compared to conventional sowing. The zero drill was more economical, that is, 79% as compared to conventional sowing (Singh et al., 2014).

Manufacturing of agricultural machinery in India is varied in nature and starts from village artisans, tinv units. cottage to small scale industries, organized tractor and agricultural machinery manufacturers including energy and processing machinery industry. Standardization and quality control measures are inadequate except in the organized sector like in tractor manufacturing. Equipment for efficient irrigation, appropriate use of pesticides, micronutrients and minimizing their excess use to protect soil health and environment is a growing concern. Selection of correct sprayer for chemical application is an important issue for effective pest and weed control. Studies indicate that 70% of the success of chemical depends on the effectiveness of its application (Malik et al., 2012). By mechanization in spraying devices, chemicals were distributed equally on the farm and reduced the quantity of waste, resulted in prevention of losses and wastage of input. It reduced the cost of production and gave higher productivity in minimum input (Das et al., 2015).

Precision in application rates for higher input use efficiency can be achieved only by improving the designs of the existing equipment. The critical operations in the crop production cycle where implementation precision has a significant role are (a) seeding/planting, (b) fertilizing, (c) chemical applications, (d) irrigation, and (f) inter-cultural operations. At present, the availability of state-of-art precision equipment for different operations is lacking. Precision is an attribute inbuilt in the functional design of a component or components of equipment. Also, desired precision is achieved through proper adjustments and operational parameters while using a mechanical gadget/device to ensure desired accuracy and efficiency.

Precision Index (PI) is based on the capability of equipment to perform a given task in an accurate manner. It is a worthwhile attribute to compare the performance of different equipment and operations to enhance the productivity of a given farm. An interdisciplinary approach among agricultural engineers, agronomists, soil scientists, and horticulturists might help in developing the qualitative and quantitative precision indices for different farm equipment. PI ought to be computed on the basis of extensive field testing of a given implement/equipment/component. lt is а mathematical and statistical measure of precision for any machinery. Before purchasing equipment, the user ought to know the PI for the equipment recommended to him. One must buy/custom-hire farm equipment with high PI. The PI can be compared for machinery irrespective of their make and type with same purpose or function of operation. Manufacturer/Supplier must apprise him about the same. Therefore, the role of testing centre/testing agency assumes critical importance in the context of adoption and propagation of precision farm equipment and machinery. Qualitative precision indices of farm equipment will be very useful for the selection of equipment.

In the present study, different make and types of seed drills, multi-crop planters, and sprayers were selected to compute their PI. There is no information available regarding computation of a quantitative PI. The purpose of study is to propose an index, that is, PI to select efficient and precise equipment for the farmers.

MATERIALS AND METHODS

Selection of suitable material and methods used for the study are briefly described under this part. Zero till seed-cum-fertilizer drills, multi-crop planters and sprayers manufactured and commercialized with different make and models by different manufacturers were selected for the study. These models are being tested and evaluated by the government testing centers as per the BIS norms and manufactured by different manufacturers.

Selection of machines

PI values were calculated for two types of functionality as sowing and plant protection and the machineries were zero seed cum fertilizer drills, planters and spraying machines (Figure 1). Five numbers of zero seed cum fertilizer drills of different make and models and a recently introduced second generation drill like happy seeder machine for direct sowing of wheat in combine harvested field were selected for the study. Various design and operational specifications of selected drill machines are shown in Table 1. Different planters such as multi crop planter, semi-automatic potato planter and automatic potato planter were selected to find their PI. A tractor operated potato planter was evaluated at Latif experiment farm and found that the field efficiency and field capacity of potato planter was 67.5% and 0.80 ha/h, respectively. Planter covered more area in less time and saved labour (Mari et al., 2002). Technical specifications like metering mechanism, metering device and metering power source were considered and shown in Table 2.

Five types of sprayers namely Gun type, Knapsack type, Electrostatic type, Boom Type and Air assisted type were selected for knowing the PI value. Electrostatic and mist blower sprayers were evaluated for deposition efficiency and biological efficacy. Spray deposition efficiency of electrostatic sprayer was very high with uniform distribution irrespective of leaf taxonomy, anatomy and morphology. The usage of chemicals was about 30 to 35% in case



Figure 1. Selected machinery.

_

Table 1. Technical specifications of selected drill machines.

Specification		Нарру				
Specification	Make 1	Make 2	Make 3	Make 4	Make 5	Seeder
Furrow openers (Nos.)	11	11	11	11	11	09
Seed metering device (Type)	Fluted roller					
Dia. size (mm) & fluted rollers (Nos.)	48.6 & 11	46.2 & 11	48.7 & 11	46.6 & 11	48.4 & 11	47.5 & 09
Fertilizer distributer (type)	Vertical disc	Fluted roller	Plate type	Fluted roller	Plate type	Fluted roller
Dia. size (mm) & metering device (Nos.)	129.3 & 11	46.2 & 11	90.0 & 11	46.6 & 11	90.0 & 11	50.0 & 09
Forward speed, km/h	3.0	3.0	3.0-5.0	3.0	3.0-5.0	2.0- 3.0

Table 2. Technical specifications of selected planting machines.

Specification	Multi-crop planter	Automatic potato planter
Power source	Tractor	Tractor
Metering mechanism (type)	Disc with notches	Picker wheel
Seed metering devices (Nos.)	04	02
Notches/Pickers on metering device (Nos.)	24	10
Disc diameter (mm)	172	-
Crop cultivated	Cotton, soybean, maize	Potato

Specification	Gun type	Knapsack	Electrostatic backpack	Boom type	Air assisted
Spray tank capacity (I)	500-1000	15	15	500	15
Power source	Tractor PTO	Lever operated	Petrol engine	Tractor PTO	Petrol engine
Operating pressure (kg/cm ²)	10-25	3.5 -4.5	4.2-4.9	15-25	4.2-4.9
Hose pipe length (m)	60-300	-	33	-	33
Nozzles (Nos.)	Single	Single	Single/Twin	16 – 18	Single/Twin
Nozzle (type)	Solid cone	Hollow cone			

Table 3. Technical specifications of selected spraying machines.





Figure 2. Field operational view of selected machines.

of electrostatic sprayer of air assisted sprayer (Subhagan et al., 2016). Important technical specifications like tank capacity, power source, operating pressure, number and type of nozzles of these sprayers are shown in Table 3.

Figure 2 shows the operational view of machines like zero till seed cum fertilizer drill, multi crop planter, happy seeder and electrostatic sprayer, selected for the calculations of their PI.

Precision attributes of different machines

To obtain the PI of selected equipment/machine, there is need to identify the different precision attributes of that machine. Figure 3 shows the various types of attributes/parameters selected for seed cum fertilizer drill, planters and sprayers. During seed drill operation, it is desired that there should not be variation in seed rate among the different furrow openers. Hence, two precision attributes one inter row variation in seed rate and another intra row

variation in fertilizer rate were identified to observe the PI of selected seed cum fertilizer drills. To compute PI for the planter, various types of attributes/parameters like missing, doubling, seed damage, seed to seed distance and depth of placing were selected. These parameters were important as they were having the direct concern with yield or output of the crop. For ensuring better yield, seed to seed distance and depth of placing the seeds should be optimum; otherwise, it puts the adverse influence on crop yield. For obtaining the PI for sprayers, five precision attributes such as volume median diameter (VMD), number median diameter (NMD), uniformity coefficient (UC), droplet density (DD) and volume of spray deposition (VSD) were identified and ranked as the important precision attributes to compute PI for sprayers.

Computation of PI (Quantitative)

While purchasing equipment, the farmer need to know the PI for the

Equipment/machine type Seed drill Planter Sprayers Volume median Missing of seeds Inter row variation in seed rate diameter (VMD) Doubling of Inter row variation Number median seeds in fertilizer rate diameter (NMD) Seed damaged Selected Uniformity Seed to seed Attributes/ coefficient (UC) Parameters distance Droplet density(DD) Tuber density Volume of spray • Depth of placing deposition (VSD)

Figure 3. Different types of selected attributes/parameters.

Table 4. Precision index of different types of sowing drill machines.

Souring drill machines	Veer of testing	Coefficient o	Precision Index	
Sowing drift machines	rear of testing	Seed Rate	Fertilizer Rate	(PI)
Make 1	2004	0.04	0.07	0.95
Make 2	2004	0.03	0.03	0.97
Make 3	2006	0.33	0.03	0.82
Make 4	2007	0.07	0.04	0.94
Make 5	2013	0.06	0.33	0.80
Happy Seeder (HS)	2014	0.09	0.15	0.88

equipment recommended to him. Obviously, the user would like to buy/custom-hire farm equipment with high PI. Manufacturer/ Supplier must apprise him about the same. Hence, the following expression is being suggested. It can be further modified/rectified based on the inputs received from stake holders.

Precision Index= 1 -
$$\left[\frac{\sum_{i=0}^{n} (VPA)_{i}}{n}\right]$$
 (1)

$$\sum_{i=0}^{n} VPA = CV1 + CV2 + CV3 + \cdots CVi$$

where n is the total number of precision attributes, VPA is the variation in precision attribute or coefficient of variation (in decimal), and CVi is the coefficient of variation of respective attributes.

Agricultural equipment are classified into five categories such as very low, low, moderate, high and very high as per PI (qualitative) values. The classification of equipment is completely based on calculated value of PI. Machine with more calculated value or close to 1 will be more precised.

RESULTS AND DISCUSSION

PI of sowing machines

Inter row variations in seed and fertilizer rate were measured at an average seed and fertilizer rate of 76.87 and 128.10 kg/ha, respectively during their testing. PI (Qualitative) of different drill machines calculated with the help of PI expression (Equation 1), are shown in Table 4. The coefficient of variance (CV) for seed rate was varied from 0.03 for Make 2 drill to 0.33 for Make 3 drill. Seed rate of second generation drill, that is, happy seeder machine was having more CV, that is, 0.09 than all other selected drills except Make 3 drill. Similarly, coefficient of variance for fertilizer rate was varied from 0.03 for drill of Make 2. to 0.33 for drill of Make 5. Fertilizer rate of happy seeder machine was having more CV, that is, 0.15 than

	Testing	Variability in							
Type of planter	year	Missing	Doubling	Fertilizer rate	Tuber Damage	Seed spacing	Tuber Density	Depth of placing	PI
Multi-crop	2014	0.20	0.28	0.04	-	-	-	-	0.83
Automatic potato	2013	0.29	0.45	-	0.16	0.09	0.10	0.08	0.80
Semi-automatic potato	1980	0.31	0.63	-	0.35	0.18	0.10	-	0.70

Table 5. Precision index of planting machines.

all other selected drills except Make 5 drill. It could be concluded that drill of Make 2, tested in the year 2004, was having the highest PI value, that is, 0.97 or 97% followed by Make 1 drill having PI value 0.95 or 95% tested in the same year. Make 5 drill tested in the year 2013 was having minimum PI value, that is, 0.80 or 80%. PI value for happy seeder machine was 0.88 or 88%, which seems to be low. This may be due to poorer working conditions of the machine, as it is operated for direct sowing of wheat crop in paddy stubble conditions.

PI of planting machines

Table 5 shows the PI of planting machines based on the variability of different attributes. The PI of multi-crop planter was observed by finding the variability of various attributes like missing, doubling and inter row fertilizer rate. The variability in doubling attribute was more that is 28% followed by missing with 20% value and produced influence on PI which was observed to be 0.83 or 83%. Inter row fertilizer rate attribute was having less effect on PI of planter due to its lesser variability, that is, 4.0%.

Variability of precision attributes, that is, missing, doubling, tuber damage, seed to seed distance tuber density and depth of placing was measured to observe the PI of semi-automatic and automatic potato planter. With the help of PI expression, PI was found to be 0.80 for automatic potato planter, tested in the year 2013. Similarly, the PI of semi-automatic planter, tested in the year 1980, was found to be 0.70. The value of PI was influenced more by attributes like doubling and missing which was having variability of 45 and 29%, respectively as compared to other attributes like tuber damage, seed to seed distance, tuber density and depth of placing which was having CV in the range of 0.08 to 0.16. In case of semi-automatic potato planter, the reason of lower PI was the higher variability in attributes like doubling, missing and tuber damage which were having variability, 0.63, 0.31 and 0.35%, respectively, found more as compared to other attributes.

PI of spraying machines

Figure 4 and Table 6 shows the CV and PI of selected

sprayers of different types calculated by using various precision attributes such as number median diameter (NMD), volume median diameter (VMD), uniformity coefficient (UC), droplets density (DD; No. of Droplets cm⁻ ²), area covered by droplets (AC; mm² cm⁻²) and volume of spray deposition (VSD; cc cm⁻²). In case of Knapsack sprayer, the variability of attributes was measured in the range of 0.30 to 1.31, influenced and being the reason of lower PI having index value 0.40. The major impact on PI of Knapsack sprayer was produced by VSD having 1.31 CV followed by NMD and DD having CV 0.55 and 0.51, respectively. PI of gun and boom type sprayer was observed having values 0.54 and 0.73, respectively. The values of CV for gun and boom type sprayer were observed in the range of 0.13-0.73 and 0.04-0.39, respectively. In gun type sprayer, maximum and minimum variability was found in DD and VMD, shared 73 and 13%, respectively. In boom type sprayer, the maximum influence on PI was produced by NMD, UC and VSD attributes, having variability 37, 32 and 39%, respectively. PI of electrostatic sprayer mounted with single as well as twin nozzle was observed to be on highest that is 0.89 followed by PI of air assisted sprayer with single and double nozzle having PI values 0.83 and 0.84, respectively. In electrostatic sprayer, the range of CV of selected attributes varied from 0.06 to 0.17 and the CV for air assisted sprayer was found in the range of 0.06 to 0.43 for UC and DD, respectively.

By comparing the PI of spraying machines, it could be instated that the field performance of electrostatic sprayer whether single or twin nozzle, was found to be efficient as compared to other spraying machines. Lower PI of Knapsack sprayer ranked it as poor sprayer due to its lower efficacy and efficiency comparing to other sprayers.

Conclusions

The following conclusions were drawn from the present study:

(1) It was concluded that seed cum fertilizer drill of Make 2, tested in the year 2004, was having the highest PI value, that is, 0.97 or 97% followed by Make 1 drill having PI value 0.95 or 95% tested in the same year.

(2) Make 4 drill tested in the year 2007 was having PI



Figure 4. Precision index of selected machines.

Table 6.	Precision	index of	different	types of	spraying	machines.
				21		

C/N	Time of Carolina		Variability in					
S/IN	Type of Sprayer	VMD	NMD	UC	DD	VSD	Index	
1	Knapsack	0.30	0.55	0.35	0.51	1.31	0.40	
2	Gun type	0.13	0.50	0.62	0.73	0.32	0.54	
3	Boom type	0.04	0.37	0.32	0.25	0.39	0.73	
4	Electrostatic single nozzle	0.14	0.09	0.08	0.14	0.08	0.89	
5	Electrostatic twin nozzle	0.12	0.11	0.06	0.17	0.08	0.89	
6	Air assisted single nozzle	0.16	0.09	0.08	0.43	0.07	0.83	
7	Air assisted double nozzle	0.11	0.11	0.06	0.43	0.07	0.84	

value 0.94 followed by Make 3 and Make 4 which were having lower PI values, that is, 0.82 and 0.80, respectively as compared to other drills of different Make. (3) From the testing of seed cum fertilizer drills, it was found that the manufactured drill machines of different Makes were having different PI values which varied from 0.80 to 0.97. Hence, it was concluded that drill machines manufactured by different Makers were not standardised as all drills of different Make were having different PI values.

(4) PI value for happy seeder machine was 0.88 or 88%, which seems to be low. This may be due to poorer

working conditions of this machine, as it operated for direct sowing of wheat crop in paddy stubble conditions.

(5) During the testing of multi-crop planter in year 2014, the variability of doubling attribute was more, that is, 28% followed by missing having 20% value and produced influence on PI which was observed to be 0.83 or 83%.
(6) PI of semi-automatic and automatic potato planter was found to be 0.70 and 0.80, respectively. The value was not much satisfactory and could be rank under average category.

(7) PI of electrostatic sprayer mounted with single as well as twin nozzle was observed to be highest, that is, 0.89 followed by PI of air assisted sprayer with single and double nozzle, that is, 0.83 and 0.84, respectively.

(8) The range of CV of selected attributes was varied from 0.06 to 0.17 and 0.06 to 0.43 for electrostatic and air assisted sprayer, respectively.

(9) Field performance of electrostatic sprayer whether single or twin nozzle, was found to be efficient as compared to other spraying machines and fairly assessed it an effective and efficient sprayer followed by air assisted sprayer.

Hence, it is concluded from the study that the PI of machine/equipment is a tool to the farmers and researchers used/helped to procure and select an optimum agricultural equipment/machine for farm use and for research intention. With the results of PI, further refinement and modification in the existing component/machine/equipment can be done from the researcher and manufacturers' sides.

CONFLICT OF INTERESTS

The authors have not declared any conflict of interests.

REFERENCES

- Anonymous (2013). Report of the sub-group on agricultural implements and machinery for formulation of 9th five year plan, Govt. of India.
- Das N, Maske N, Khawas V, Chaudhary SK, Dhete RD (2015). Agricultural Fertilizers and Pesticides Sprayers - A Review. International Journal for Innovative Research in Science and Technology 1(11):44-47.
- Kulkarni SD (2012). Mechanization of agriculture Indian scenario, Central Institute of Agricultural Engineering (CIAE), Bhopal, India. P 19.
- Malik RK, Pundir A, Dar SR, Singh SK, Gopal R, Shankar PR, Singh N, Jat ML (2012). Sprayers and spraying techniques - A manual, CSISA, IRRI and CIMMYT.CG Block, National Agricultural Science Centre (NASC) Complex, DPS Marg, New Delhi 110 012, India. P 20.
- Mari GR, Memon SA, Leghari N, Brohi AD (2002). evaluation of tractor operated potato planter. Pakistan Journal of Applied Sciences 2(9):889-891.
- Singh P, Singh S, Singh BR (2014). Performance of Zero-Till Drill for Wheat Cultivation at Farmer's Fields. International Journal of Science and Research 3(7):2078-2084.
- Subhagan SR, Dhalin D, Khtatawkar DS (2016). Comparative evaluation of electrostatic sprayer with powered mist blower. International Journal of Engineering Research and Development 12(8):04-11.

Related Journals:



















www.academicjournals.org