

*Full Length Research Paper*

## **Effects of tractor forward velocity on soil compaction under different soil water contents in Tunisia**

**Chiheb Khemis<sup>1,2\*</sup>, Khaoula Abrougui<sup>1</sup>, Karim Gabsi<sup>3\*</sup>, Roua Amami<sup>1</sup>, Waweru Geoffrey<sup>4</sup>, Eunice Mutuku<sup>2</sup>, Wim Cornelis<sup>2</sup> and Sayed Chehaibi<sup>1</sup>**

<sup>1</sup>UR 13AGR03: Conventional and Organic Vegetable Crops Unit, Higher Institute of Agricultural Sciences, Sousse University, 4042 Chott Meriem, Tunisia.

<sup>2</sup>Department of Environment – UNESCO Chair on Eremology, Ghent University, 9000 Ghent, Belgium.

<sup>3</sup>Higher School of Engineers, Jendouba University, 9070 Medjez El Bab, Tunisia.

<sup>4</sup>Department of Land Resources Planning and Management Jomo Kenyatta University of Agriculture and Technology, P. O. Box 62000-00200, Nairobi.

Received 13 August, 2019; Accepted 19 September, 2019

Africa is the second continent suffering from soil compaction; studies of this phenomenon must be multiplied in order to overcome this problem. Very few studies have been conducted in Tunisia to understand soil compaction, its causes and its effect on soil properties. The research was conducted on experimental field at the Higher Institute of Agronomy of Chott Mariam, Sousse, Tunisia. The main objective of this study was to evaluate the effect of different speed of tractor compaction on soil, that is, no compaction (C0), speed 1 (C2) = 4 km h<sup>-1</sup>, speed 2 (C3) = 9 km h<sup>-1</sup> on the hydraulic and physical properties of a silt loam texture under three natural moisture conditions: H0, H1 (15 days later), and H2 (30 days later). Each test run was limited to one pass. Undisturbed soil cores were collected in the topsoil (0-10 cm), at 10-20 cm and in the subsoil (20-30 cm) below the trace of the wheel at site. Soil compaction level was determined by penetration resistance using a penetrometer. Bulk density was then determined to evaluate the impact of the two tractor frequency passages at the three moisture conditions on soil compaction. For initial soil (C0), bulk density was 1.38 Mg m<sup>-3</sup>. After the tractor pass, the highest degree of compaction was observed with tractor speed 1 (C1) which significantly changed soil bulk density resulting in values of up to 1.74 Mg m<sup>-3</sup> in the topsoil and compacted subsoil under H1, which is significantly above the critical value of 1.6 Mg m<sup>-3</sup> for soils with clay content below 17.5%. The high degree of compaction significantly affected penetration resistance of topsoil. The results demonstrate that different degrees of soil compaction under different moisture levels could greatly influence physical properties in different ways. Even under relatively low water contents, that is, below field capacity, substantial top soil compaction was induced after one tractor pass.

**Key words:** Soil compaction, tractor speed, soil moisture, penetration resistance, bulk density.

### **INTRODUCTION**

The world population is projected to exceed 9 billion by 2050 (FAO, 2017) with a higher probability of double increase in Africa (Guengant and May, 2013). This

implies that food production has increase by 70%. In order to reach this target, intensive agriculture using large machinery for harvesting, cropping and field operations

will increase considerably generate the risks of soil compaction leads to soil degradation (Bargali et al. (2019). This problem was expected as one of the main factors of soil degradation affecting an area of 68 Mha (Oldeman, 1992). Soil compaction is one of the principal causes of environmental and agronomic problems. Compaction can lead to erosion, flooding, leaching of chemicals to water bodies, surface water runoff and emission of greenhouse gases (Lull, 1959, Soane and Van Ouwerkerk, 1995). Soil compaction generated by machinery traffic affects the essential ecological soil functions by reducing total porosity, air capacity, saturated hydraulic conductivity, water infiltration and proportion of larger pores (Alakukku et al., 2003, Alaoui et al. 2011, Nawaz, Bourrie et al. 2013). In West Africa, soil compaction reduced crop yield by 40% to 90% (Charreau 1972, Kayombo and Lal 1994). Soil compaction can be natural caused by internal forces, such as freezing, drying, swelling and shrinking (Jabro et al. 2014) or artificial caused by external forces applied by vehicles and various equipment for field operations (Cohron, 1971; Greene and Stuart, 1985; Schjønning et al., 2015; Ren et al., 2019). Depending on external stress, soil can react elastically up to a certain limit of force; beyond that limit, any incremental stress conduct to plastic deformation (Horn et al., 1995; Destain, 2014).

Artificial soil compaction is influenced by mechanical parameters related to agricultural machines and implement used expressed by axle load, frequency of the machine passages, number of passes, tyre number and architecture, velocity, tyre inflation pressure and soil tyre interaction (Chamen et al., 2003; Hamza and Anderson, 2005; Arvidsson and Keller, 2007; Sakai et al., 2008; Barbosa and Magalhães, 2015; Khemis et al., 2017; D'Hose et al., 2019). Although the effect of frequency of machine passages is of much lesser consequence than that of other mechanical factors, compaction is depending on the applied stress time. Thus, although there are dynamic effects such as bouncing and acceleration which might increase stress with speed, on average, the faster one goes over the soil, the less effect it will have (Alakukku et al., 2003, Khodaei et al., 2015). Additional to mechanicals parameters affecting soil compaction, water content is one of the most important factors which depend on soil compaction phenomena. Its effects on the mechanical behavior of soils have been the subject of many studies (Horn and Albrechts, 2002; Hamza et al., 2011; Nawaz et al., 2013, Destain, 2014). All authors observe that mechanical parameters are strongly affected by soil moisture content. However, our understanding of the effect of tractor speed on soil compaction and its impact on arable soils is still limited.

In soil compaction research, the major focus has been on the effect of axle load, number of passes and tire inflation pressure. The main objective of this study was to examine the impact of the machine speed on physicals properties of soil under different soil water contents.

## MATERIALS AND METHODS

The experimental area was at the Higher Institute of Agronomic Sciences Chatt-Mariem, Sousse University, Tunisia (35°54'40.2"N 10°33'24.3"E). The soil has a silty loam texture (21% clay, 30 % silt, 48 % sand) down to 0.3m depth. The principal crop of the field was a biological potato. Conventional tillage was employed to till the soil. Climate of the region is dry with warm summers, annual precipitation of 558 mm and a mean annual temperature of 21°C. Soil organic matter at the experimental area was 1.2%. Two speeds of tractor under three levels of water contents conditions were used in a completely randomized design (9 treatments) as follows: (C0: control, C1: speed 1= 4 km h<sup>-1</sup>, C2: speed 2 = 9 km h<sup>-1</sup>) (H0 (t=0), H1 (after 15 days), H2 (after 30 days)). The tractor exported for this study was a Foton TA700 with total weight of 3.100 kg, power capacity of 51 kW and standard wheel-drive with a single rear tire. The measurements were conducted and samples were picked up from the same field in the Higher Institute of Agronomic Sciences Chatt-Mariem. Undisturbed soil cores (5 cm high and 5 cm in diameter) were arbitrary picked up at depths of 10, 20 and 30cm. Thus, in total 81 soil cores were collected. Penetration resistance was evaluated at depths of 10,20,30,40 and 50cm. In some cases, mainly for H0, the soil was too dry and strong below the normal depth of tillage (around 30 cm) for penetrations to be carried out. In these situations, only the plough layer was measured. The organic matter content was quantified by wet oxidation. Sample collection for measurement of bulk density and water content were made on a region of approximately 1.5 m<sup>2</sup>. Penetrometer measurements were carried out on a surface of about 3 m radius from the centre of the sample collection area for each treatment. Therefore, all samples and all measurements were conducted as approximately as possible, to decrease the effects of spatial variability to a minimum.

### Penetration resistance

The penetration resistance of the soil ( $r_p$ ) is considerably used to estimate the degree of compaction (Bouwman and Arts, 2000; Sharifi et al., 2007). It is the resistance of soil to the force of penetration per unit area expressed in Nm<sup>-2</sup> or in MPa. Penetration resistance was assessed with a hand-driven penetrometer (Eijkelkamp, Giesbeek, The Netherlands). This device combines an electronic penetrometer with a built-in datalogger for storage and processing. It measures the mean vertical stress required for penetration of a steel cone of 11.28 mm. The penetration depth is measured continuously as the cone is pushed into the soil. The measuring range is 0-10 MPa (with a resolution of 0.01 MPa), and the measuring depth is from the surface down to 0.8 m (vertical resolution of 0.01 m). The penetration resistance is greatly influenced by soil water content, soil texture, organic matter content, speed of penetration, and the length and tip angle of the cone. The PR at about 108 measurement points was measured; the penetration speed was 0.02 m. s<sup>-1</sup> with a 60° cone of 1 cm<sup>2</sup>.

\*Corresponding author. E-mail: khemis.chiheb@iresa.agrinet.tn.

**Table 1.** Mean values of selected physical properties of a silt loam soil in the centre of Tunisia (ChottMeriem site) and soil water contents at the time of the wheeling experiment with tractor speed 1 (C1), tractor speed 2 (C2) and initial soil condition (C0) under dry (H0) and moist (H1), (H2) soil conditions.

Depth (m)	Soil water content (w/w)	Particle density (Mgm <sup>-3</sup> )	Sand 0.05-2 mm (%)	Silt 0.002-0.05 mm (%)	Clay <0.002 mm (%)
0 - 0.1	H0:3.89	2.65	60	30	10
	H1: 12.02				
	H2: 9.75				
0.1-0.2	H0: 4.95	2.65	68	21	11
	H1: 10.3				
	H2: 10.25				
0.2-0.3	H0: 5.08	2.65	69	21	08
	H1: 7.62				
	H2: 9.38				

### Soil bulk density and water content

Bulk density was evaluated on soil samples picked out by using a portable soil sampler with metal cylinders of approximately 5 cm height. Each cylinder was then locked at both ends with pvc covers and was then placed in a polythene sac that was closed tightly. This ensured that the samples would stay at their field water content. Generally, three replicate samples were picked out from each layer although in a few cases there were more. All samples were dried at same temperature of 105 °C for 24 h in an oven. The dry mass of the soil divided by the cylinder volume provided the bulk density, BD (Mgm<sup>-3</sup>). The gravimetric water content, W (kgkg<sup>-1</sup>) was evaluated as the mass of water in the soil sample divided by the mass of the dry soil.

### Statistical analysis

Mean values, standard deviations and standard errors are reported for each of the measurements. ANOVA was used to assess the effects of compaction on the measured variables. When ANOVA indicated a significant F -value, multiple comparisons of mean values were performed by the least significant difference method (LSD). The SPSS software 20 package (2011) was used for all of the statistical analyses.

## RESULTS AND DISCUSSION

### Soil characteristics

Using the USDA/Soil Taxonomy texture triangle classification system, the results corresponding to soil texture analyses (Table 1) classified the soil as a silt loam soil. It had a similar percent of sand, silt and clay and the same particle density in each layer. Soil compaction level and moisture content significantly affected the bulk density. The higher impact of tractor speed is noticed in the top soil, which indicates that the impact of frequency of tractor passages was not transmitted to the subsoil. These results agree with those obtained by Horn et al.


(1989). However, under the initial soil conditions (C0) and humidity H1, dry bulk density was already 1.32, 1.48 and 1.45 Mgm<sup>-3</sup> for depths 0-0.10, 0.10-0.20 and 0.20-0.30 m, respectively. Increases in soil bulk density caused by frequency of tractor passages were higher at lower speed of tractor. For example, for C1, soil bulk density increased by 21% for the topsoil (Figure 1).

Soil bulk density increased with depth for all the treatments. The effect of the frequency of tractor passages on dry bulk density was significant ( $p < 0.05$ ). Increase in soil bulk density caused by tractor speed was higher at higher values of soil moisture content. The effects of frequency of tractor passages were more noticeable in the top soil especially for 0.10 to 0.15 m, which indicates that the impact of speed was not transmitted to the subsoil.

These results agree with those obtained by Horn et al. (1989b), Çarman (1994) and Ansoorge and Godwin (2008). The results also support the suggestion by Kayombo and Lal (1994) that speed of tractor is an important factor in soil compaction. Several studies have demonstrated that the increase in passage frequency will have a cumulative compaction effect (Etana and Håkansson, 1994). Dry bulk density always increased with a lower speed of tractor at depth of 0.05 to 0.20 m, but there was no significant difference between the treatments at subsoil layer more than 0.25 m depth (Alakukku et al., 2003).

### Penetration resistance

Penetration resistance data had a normal distribution. The analysis of variance revealed that the effects of tractor speed on soil penetration resistance at the first 0.10 m depth were all highly significant ( $p < 0.001$ ) (Table 2).




**Figure 1.** Bulk density for three level of compaction with varying the frequency of tractor passages (C0: no compaction, C1= speed 1 C2= speed 2) under three moisture conditions (a) H0 (t=0), (b) H1 (after 15 days), (c) H2 (after 30 days). The same type of tractor was used for all the treatments with a tyre inflation pressure of 1500 kg/cm<sup>2</sup>.

**Table 2.** ANOVA results for soil penetration resistance influenced by tractor speed.

Source of change	DF	Frequency	Significance
Speed (m.s <sup>-1</sup> )	2	21,053	0.000
Depth (cm)	1	62,006	0.000
Humidity	2	3,032	0.000
Speed * Depth	2	1,830	0.001
Depth*Humidity*Speed	4	1,031	0.004

\*\* , \* Significant at the 1 and 5% level respectively; ns, Non-significant at the 5% level.



**Figure 2.** Penetration resistance at different depths after (C0: no compaction, C1= speed 1 C2= speed 2) under three moisture conditions (a) H0 (t=0), (b) H1 (after 15 days), (c) H2 (after 30 days) under moist (H0) and dry (H1):(left) and corresponding soil water content (right).

The interaction between Depth\*Humidity\*Speed was highly significant. The comparison of the mean

penetration resistance profile for different soil moisture content H0, H1 and H2 is shown in Figure 2. As reported

by several studies (Taylor 1971; Bouwman and Arts, 2000; Horn and Rostek, 2000; Servadio et al., 2005), penetration resistance increases with increasing bulk density. The effect of tractor speed on penetration resistance was significant ( $p < 0.01$ ) for the top soil. The largest difference in penetration resistance between treatments was observed in the top 0.15 m, where it was substantially higher for C1 than then other treatment. Indeed, at 5 cm depth, the values of penetration resistance soil resistance were 0.5, 0.9 and 1.5 MPa, respectively for treatments C0, C2 and C1 and at 15 cm depth, the values were up to it 1.2, 3.8 and 4.3 MPa respectively for the same treatments. Similar results have been reported by Khodaei et al. (2015). Similar study was conducted by Çarman (1994), which conclude that increasing of approximately 221% in forward velocity caused a decrease in cone index by 15%.

## Conclusion

The investigation on the effects on some soil qualities following passages with two levels of tractor frequency, carried out in central Tunisia, has shown that frequency of tractor passages corresponding to speed 4 km h<sup>-1</sup> resulted in significant soil compaction, especially for wet conditions. Bulk density and penetration resistance measurements confirmed these results. Even under water contents below or near field capacity, substantial top soil compaction was induced after one tractor pass. Tractor speed had a significant effect at 15 cm depth and no difference between treatments in the subsoil layer which was confirmed by Arvidsson and Keller (2007). Within the limits of the experimental conditions, it can be concluded that there is a direct relation between the frequency of tractor passages and the degree of compaction in the topsoil. Particularly, lower speed resulted in significant increases in bulk density and penetration resistance in the top 15 cm.

## CONFLICT OF INTERESTS

The authors have not declared any conflict of interests.

## REFERENCES

- Alakukku L, Weisskopf P, Chamen T, Tijink F, Linden JP, Pires S, Sommer C, Sommer C, Spoor G (2003). "Prevention strategies for field traffic-induced subsoil compaction: a review: Part 1. Machine/soil interactions." *Soil and Tillage Research* 73(1-2):145-160.
- Alaoui AJ, Lipiec, Gerke HH (2011). "A review of the changes in the soil pore system due to soil deformation: A hydrodynamic perspective." *Soil and Tillage Research* 115:1-15.
- Ansorge D, Godwin RJBE (2008). "The effect of tyres and a rubber track at high axle loads on soil compaction—Part 2: Multi-axle machine studies." 99(3):338-347. <https://doi.org/10.1002/ldr.3394>
- Arvidsson J, Keller T (2007). "Soil stress as affected by wheel load and tyre inflation pressure." *Soil and Tillage Research* 96(1-2):284-291.
- Barbosa LAP, Magalhães PSG (2015). "Tire tread pattern design trigger on the stress distribution over rigid surfaces and soil compaction." *Journal of Terramechanics* 58:27-38.
- Bargali SS, Padalia K, Bargali K (2019). "Effects of tree fostering on soil health and microbial biomass under different land use systems in central himalaya." *Land Degradation and Development* 30:16.
- Bouwman L, Arts WBM (2000). "Effects of soil compaction on the relationships between nematodes, grass production and soil physical properties." *Applied Soil Ecology* 14(3):213-222.
- Çarman K (1994). "Tractor forward velocity and tire load effects on soil compaction." *Journal of Terramechanics* 31(1):11-20.
- Chamen T, Alakukku L, Pires S, Sommer C, Spoor G, Tijink F, Weisskopf P (2003). "Prevention strategies for field traffic-induced subsoil compaction: a review: Part 2. Equipment and field practices." *Soil and Tillage Research* 73(1-2):161-174.
- Charreau C (1972). "Problèmes posés par l'utilisation agricole des sols tropicaux par des cultures annuelles." *L'Agronomie Tropicale. Série 2, Agronomie Générale. Etudes Techniques* 27(9):905-929.
- Cohron G (1971). "Forces causing soil compaction." *Compaction of Agricultural Soils* 106:122.
- Destain MF (2014). *La compaction des sols agricoles en Wallonie*, SPW. P. 53. <https://orbi.uliege.be/handle/2268/170422>
- Etana A, Håkansson I (1994). "Swedish experiments on the persistence of subsoil compaction caused by vehicles with high axle load." *Soil and Tillage* 29(2-3):167-172.
- Food and Agriculture Organization (FAO) (2017). *The future of food and agriculture—Trends and challenges*. Annual Report 296:1-180.
- Greene WD, Stuart WB (1985). "Skidder and tire size effects on soil compaction." *Southern Journal of Applied Forestry* 9(3):154-157.
- Guengant JP, May J (2013). "Africa 2050: African demography." Available at: [http://horizon.documentation.ird.fr/exl-doc/pleins\\_textes/divers13-07/010059333.pdf](http://horizon.documentation.ird.fr/exl-doc/pleins_textes/divers13-07/010059333.pdf)
- Hamza M, Anderson W (2005). "Soil compaction in cropping systems: A review of the nature, causes and possible solutions." *Soil and Tillage Research* 82(2):121-145.
- Hamza M, Al-Adawi SS, Al-Hinai KA (2011). "Effect of combined soil water and external load on soil compaction." *Soil Research* 49(2):135-142.
- Horn R, Albrechts C (2002). Stress strain effects in structured unsaturated soils on coupled mechanical and hydraulic processes. In 2002 American Society of Agricultural and Biological Engineers (ASAE) Annual Meeting P 1.
- Horn R, Rostek J (2000). Subsoil compaction processes – state of knowledge. *Advances in GeoEcology*. Reiskirchen: Catena P 32.
- Horn R, Blackwell PMS, White R (1989). "The effect of speed of wheeling on soil stresses, rut depth and soil physical properties in an ameliorated transitional red-brown earth." *Soil and Tillage Research* 13(4):353-364.
- Horn R, Lebert M, Burger N (1989b). *Die mechanische Belastbarkeit von Böden als Pflanzenstandort*. Materialband Nr. 73, Bayerisches Staatsministerium für Landwirtschaft und Umwelt.
- Horn R, Domzal H, Slowinska-Jurkiewicz A, van Ouwerkerk C (1995). "Soil compaction processes and their effects on the structure of arable soils and the environment." *Soil and Tillage Research* 35(1-2):23-36.
- Jabro J, Iversen WM, Evans RG, Allen BL, Stevens WB (2014). "Repeated freeze-thaw cycle effects on soil compaction in a clay loam in Northeastern Montana." *Soil Science Society of America Journal* 78(3):737-744.
- Kayombo B, Lal R (1994). Responses of tropical crops to soil compaction. *Developments in Agricultural Engineering*, Elsevier 11:287-316.
- Khemis C, Abrougui K, Ren L, Mutuku EA, Chehaibi S, Cornelis W (2017). Effects of tractor loads and tyre pressures on soil compaction in Tunisia under different moisture conditions. EGU General Assembly Conference Abstracts.
- Khodaei M, Fattahi SH, Navid H (2015). "Evaluation of corn planter under travel speed, working depth, pressure wheel and cone index." *Agricultural Engineering International: CIGR Journal* 17(4):73-80.
- Lull HW (1959). *Soil compaction on forest and range lands*, Forest Service, US Department of Agriculture.

- Nawaz MF, Guilhem B, Fabienne T (2013). "Soil compaction impact and modelling. A review." *Agronomy for Sustainable Development* 33(2):291-309.
- Oldeman LR (1992). Global extent of soil degradation. Bi-Annual Report 1991-1992/ISRIC, ISRIC: pp. 19-36.
- Ren L, D'Hose T, Ruysschaert G, De Pue J, Meftah R, Cnudde V, Cornelis W (2019). "Effects of soil wetness and tyre pressure on soil physical quality and maize growth by a slurry spreader system." *Oil and Tillage Research* 195:104344.
- Sakai H, Nordfjell T, Suadicani K, Talbot BE, Bøllehuus NE (2008). "Soil compaction on forest soils from different kinds of tires and tracks and possibility of accurate estimate." *Croatian Journal of Forest Engineering: Journal for Theory and Application of Forestry Engineering* 29(1):15-27.
- Schjøning P, van den Akker J, Keller T, Greve MH, Lamandé M, Simojoki A, Stettler M, Arvidsson J, Breuning-Madsen H (2015). Driver-pressure-state-impact-response (DPSIR) analysis and risk assessment for soil compaction-a European perspective. *Advances in Agronomy*, Elsevier 133:183-237.
- Servadio P, Marsili A, Vignozzi N, Pellegrini S, Pagliai M (2005). "Effects on some soil qualities in central Italy following the passage of four wheel drive tractor fitted with single and dual tires." *Soil and Tillage Research* 84(1):87-100.
- Sharifi A, Godwin RJ, O'Dogherty MJ, Dresser ML (2007). "Evaluating the performance of a soil compaction sensor." *Soil Use and Management* 23(2):171-177.
- Soane B, Van Ouwerkerk C (1995). "Implications of soil compaction in crop production for the quality of the environment." *Soil and Tillage Research* 35(1-2):5-22.
- Taylor HM (1971). Effects of Soil Strength on Seedling Emergence, Root Growth and Crop Yield. In: Barnes, K.K., Carleton, W.M., Taylor, H.M., Throckmorton, R.I. and van den Berg, G.E., Eds., *Compaction of Agricultural Soils*, American Society of Agricultural Engineers, St. Joseph pp. 292-305.