

*Full Length Research Paper*

# Optimizing tilt angles and orientations of solar panels for Kuala Lumpur, Malaysia

**B. R. Elhab, K. Sopian, Sohif Mat, Ch Lim, M. Y. Sulaiman, M. H. Ruslan, Omidreza Saadatian\***

Solar Energy Research Institute (SERI), Level 3, Perpustakaan Tun Sri Lanang, Universiti Kebangsaan Malaysia, 43600 Bangi, Selangor, Malaysia.

Accepted 20 June, 2012

**Shading of solar panels drastically reduces the solar collector's efficiency " $\eta$ " by reducing cell power " $P_{MP}$ ", and altering the short circuit-current " $I_{SC}$ ", the open-circuit voltage " $V_{OC}$ ", and the fill factor "FF". Therefore, the orientation and tilt angle of solar collectors play an important role in minimizing shading and consequently in increasing solar collector's efficiency. A mathematical methodology including Cooper's equation and Visual Basic Application (VBA) programming in Microsoft Excel was utilized to determine optimum tilt angles for solar collectors installed in Kuala Lumpur, Malaysia. The mathematical approach was devised to determine the optimal arrangement in flat fields, field with steps and inclined field. The result indicates that the worst shading effects happens during December and an optimum flat distance between solar collector rows for a flat field is 2.66 m for a 2 m high collector meanwhile for field with steps and inclined field, the arrangement of solar panel is depended on slope or tilt angle  $\beta$  which is presented in relevant graphs. The result is useful for the contractors, developers and consulting firms who are running projects in Kuala Lumpur, Malaysia.**

**Key words:** Solar panel, optimizing distance, optimum tilt angle.

## INTRODUCTION

Solar energy is one of the cleanest, emission free and sustainable energy which has been introduced as a remedy to combat the millennium environmental crises (Ozbalta and Kartal, 2010). Use of renewable energy is no longer a luxurious gesture of developed countries; developing countries in Africa are moving forward to use renewable energy (Ambali et al., 2011). The solar energy is not only found to be a useful source of energy for urban areas, but is also an excellent solution to cater the energy needs of remote and rural areas (Simalenga and Maliwichi, 2011). In this system, a solar collector serves to capture the incident solar energy, and convert it into a more suitable form of energy such as electricity or heat (Chong and Wong, 2009). Solar collectors provide a means by which the converted energy may be transported to the point of usage (Ucar and Inalli, 2008). There are two types of solar collectors that convert solar

rays to electricity and heat, namely, photo voltaic (PV) and solar thermal (He et al., 2011). Both of these two systems will fail to perform well if they face shading effects (David, 2011). Shading drastically reduces the solar collector's efficiency " $\eta$ " by reducing cell power " $P_{MP}$ ", and altering the short circuit-current " $I_{SC}$ ", the open-circuit voltage " $V_{OC}$ ", and the fill factor "FF" (Partain and Fraas, 2011). The shading on a collector may be cast by its neighbor and/or by a fence, and is dependent on the spacing between collectors, and on collector height, row length, tilt angle and latitude location (Joe, 2005; Appelbaum and Bany, 1979).

However, large scale solar energy systems often employ multiple rows of collectors on a horizontal surface (Armenta et al., 2011). Usually, these rows will be along an east-west axis with the collectors tilted toward the equator (Mustaffa and Yeoh, 2011). When the rows are relatively far apart, there is little shading (Yoo and Manz, 2011). Nevertheless, in some applications (for example, a building roof), the space for installation is limited (Muhammad-Sukki et al., 2011). Relatively close spacing

\*Corresponding author. E-mail: [omid.saadatian@gmail.com](mailto:omid.saadatian@gmail.com).

may be considered as a solution. Moreover, it is important to be able to determine the shadow caused reduction in net radiation flux on the collectors accurately.

This study aims to utilize a mathematical approach to determine the optimal arrangement of the solar panels in flat fields, field with steps and inclined field.

## THEORY AND FRAMEWORK

The sun appears to move in a circular orbit around the earth when viewed from a location on the earth (Dole, 1962). Although, this view is physically incorrect, it is convenient and is used for the purposes of terrestrial solar design (Bird, 1983). The sun is assumed to be located on the celestial (Bird, 1983). This is an imaginary sphere centered at the earth's center and located at a sufficiently large distance from the earth that the locations of the sun. A body moving on sphere has two degrees of freedom in its motion. This study specifies the two degrees of freedom by angles, and two angles are sufficient information to locate the sun on the celestial sphere at any time.

The altitude angle and azimuth angle are two important parameters for solar design projects (Guo et al., 2012). The azimuth angle is measured in the horizontal plane between the due-south direction and the projection of the sun-earth line onto the horizontal plane. Azimuth angles have a sign convention, as do other solar angles. The altitude angle depends on three fundamental angles: the solar declination ( $\delta$ ), the latitude ( $\phi$ ), and the solar hour angle ( $\omega$ ) (Liu and Jordan, 1960) (Figure 1).

The solar declination angle is the same as the latitude at which the sun is directly overhead on a given day. These values of latitude lie between the tropics of Cancer and Capricorn and have a variation of  $\pm 23.5^\circ$  during a year (Goswami and Kreider, 2000). Alternatively, the declination can be thought of as the angle between the overhead point for an observer on the equator and the position of the sun at noon on a given day (Goswami and Kreider, 2000). This is equivalent to the earlier definition. The solar declination angle varies slowly and can be considered constant for a specific day.

The solar azimuth angle measures the relation of the sun facing south, depending on the same three angles as the solar altitude angle (Shibayama and Wiegand, 1985). The following equation can be used to calculate the solar azimuth angle:

$$\gamma = \sin^{-1} \left[ \frac{\cos \delta * \sin \omega}{\cos \alpha_s} \right] \quad (1)$$

The azimuth angle is  $>90^\circ$  for some hours of the day when the length of day is greater than 12 h. Therefore, equation (1) must also be evaluated for the time of year for which a calculation is being made. Near sunrise and

sunset on days between March 21 and September 21, the azimuth angle is  $>90^\circ$ .

## METHODOLOGY

The study employs a theoretical approach embedding a mathematical methodology including Cooper's equation and Visual Basic Application (VBA) programming in Microsoft Excel. Avoiding shadow is inevitable and shadow's length changes from infinity at sunset and sunrise to minimum at noon time. Moreover, the length of the shadow is the tallest length at winter for the northern hemisphere. On the flat field, the solar panels are fixed in horizontal level in rows after each other by distance ( $x$ ). Those panels have a tilt angle of ( $\beta$ ) width and length of ( $l$ ). Therefore, the ratio of the required distance to obtain the optimum arrangement, that is, arranging the rows in a way that no shadow falls off the first row on the followed row, will be calculated by the following formula (Figure 2):

$$\frac{x}{l} = \frac{\sin \beta}{\tan \alpha} = + \cos \beta \quad (2)$$

Referring to Duffe and Beckman formula:

$$\sin \alpha = \cos \phi \times \cos \delta \times \cos \omega + \sin \phi \times \sin \delta \quad (3)$$

Solar altitude angle can also be calculated as:

$$\cos \theta_z = \sin(90 - \theta_z) = \sin \alpha \quad (4)$$

The solar latitude for our case study in Kuala Lumpur is  $\phi = 3.1$ . In this formula,  $\omega$  is the hour angle which is chosen at 8:00 am ( $15^\circ$  per hour time, 3 h before noon). The hour angle ( $-60$ ) negative at morning and  $\delta$  is given as follows. In this formula,  $n$  is the day of the year:

$$\delta = 23.54 \times \sin \left( 360 \frac{284+n}{365} \right) \quad (5)$$

For field with steps, the solar panels are arranged in rows after each other where a new row is elevated behind another row by a height ( $y$ ) and a distance of ( $x$ ). For avoiding shading, one can use the following formulas (Figure 3):

$$\frac{y}{l} = \sin \beta + \tan \alpha \left( \cos \beta - \frac{x}{l} \right) \quad (6)$$

For inclined filed (Figure 4), if there is a slope in the land surface of angle ( $\gamma$ ), the slope angle of solar conversion unit would be relative to the level of inclined land ( $S$ ), where:

$$\beta = s + \gamma \quad (7)$$

Therefore, the ratio required to obtain the optimum arrangement and to avoid the shadow fall of first surface on the second ( $x$ ) to the length of the solar collector ( $l$ ), is:




Figure 1. Solar altitude angle and solar azimuth angle.




Figure 2. Diagram of flat field.

$$\frac{x}{l} = \left[ \cos(S + \lambda) + \frac{\sin(S + \lambda)}{\tan \alpha} \right] \left/ \left[ 1 + \frac{\tan \lambda}{\tan \alpha} \right] \right. \quad (8)$$

$$\cos \theta = \sin \gamma \sin \varphi \cos \beta - \sin \gamma \cos \varphi \sin \beta \cos \omega + \cos \delta \cos \varphi \cos \beta \cos \omega + \cos \delta \sin \varphi \sin \beta \cos \omega + \cos \delta \sin \beta \sin \gamma \sin \omega \quad (9)$$

## RESULTS AND DISCUSSION

### Flat field

This study analyzed the effects of tilted angle to different degrees, aiming to get the optimum angle between the angles. For that, the declination was figured out on the 15th of every month in Kuala Lumpur city (Figure 5).

Knowing the solar declination angle assists in




Figure 3. Field with steps.




Figure 4. Inclined filed.

calculating the zenith angle ( $\theta_z$ ) and the hour angle (Table 1). In this study, (8.00 am) hour angle was selected.

By knowing these variables, and the length of the

collectors and the slope angle of the collector, we can obtain the height of the collector and then the distance between the collectors.

The results obtained for the flat field is presented in Figure 6. The biggest distance is needed in December,




Figure 5. Kuala Lumpur solar declination.

Table 1. Summary of data for flat field.

Day of month	Declination ( $\delta$ )	Hour angle ( $\omega$ )	Zenith angle ( $\theta_z$ )	Solar altitude ( $\alpha$ )
15 <sup>th</sup> January	-21.27	-60	63.49	26.51
15 <sup>th</sup> February	-13.28	-60	61.71	28.29
15 <sup>th</sup> March	-2.82	-60	60.25	29.75
15 <sup>th</sup> April	9.415	-60	59.92	30.1
15 <sup>th</sup> May	18.8	-60	60.68	29.31
15 <sup>th</sup> June	23.31	-60	61.36	28.64
15 <sup>th</sup> July	21.52	-60	61.1	28.93
15 <sup>th</sup> August	13.78	-60	60.17	29.83
15 <sup>th</sup> September	2.22	-60	59.93	30.06
15 <sup>th</sup> October	-9.59	-60	61.08	28.92
15 <sup>th</sup> November	-19.15	-60	62.97	27.03
15 <sup>th</sup> December	-23.34	-60	64.04	25.95

when the altitude angle is the smallest value. Moreover, at any angle of slope angle, the distance increases in this month.

### Field with steps

Value of the steps that should be elevated in the frontal row by a height ( $y$ ), and the distance separating the rows taken from the previous case at the maximum distance ( $x = 2.68$  m) are presented in Figure 7. The height ( $y$ ) changes by altering the solar altitude angle

during the year; it also depends on the slope angle.

The results shows that the maximum height of ( $y$ ) is in December and the minimum is in September. The height ( $y$ ) under  $10^\circ$  slope is very small and by increasing the slope angle, the height ( $y$ ) increases.

### Inclined field

The third case when the field is inclined by angle ( $\lambda$ ), knowing the inclined angle, we can know the slope angle.




Figure 6. The distance between collectors on flat field area.




Figure 7. The height of the next row above frontal row by (  $y$  ).

The ratio required to arrange the rows collectors and avoid the shadow fall of the first surface on the second

(  $x$  ) to the length of solar collector (  $l$  ), is the solar altitude angle during the year. Figure 8 shows the ratio




Figure 8. The distance between collectors in inclined field.

between the solar altitude angle and the distance between collectors on the 15th of each month in a year.

## Conclusion

The result indicates that the worst shading effects happens during December and an optimum flat distance between solar collector rows for a flat field is 2.66 m for a 2 m high collector, meanwhile, for field with steps and inclined field, the arrangement of solar panel depends on slope or tilt angle  $\beta$  which is presented in relevant graphs. The suitable angle for Kuala Lumpur location is ( $\beta = 10^\circ$ ).

It is also concluded that the tilting angle of a solar collector should be appropriate to receive maximum solar radiation and to avoid shading. Moreover, the spacing between solar rows must be taken in account in large scale solar system.

**Nomenclature:**  $\delta$ , Declination angle;  $n$ , day of the year;  $\phi$ , latitude;  $H$ , collector height;  $\beta$ , tilt angle;  $\gamma$ , surface azimuth angle;  $\beta_i$ , collector tracking axis incident angle;  $\theta_i$ , incident angle for surface with slope;  $x$ , distance between collectors;  $l$ , length of collectors;  $y$ , the height of next row elevates above frontal row;  $\alpha$ , solar altitude angle;  $\omega$ , hour angle;  $\theta_z$ , Zenith angle;  $\theta$ , angle of incident;  $\lambda$ , the slope angle of the land surface;  $R_b$ , ratio of beam radiation on collector surface.

## REFERENCES

- Ambali A, Chirwa PW, Chamdimba O, Zyl WHv (2011). A review of sustainable development of bioenergy in Africa: An outlook for the future bioenergy industry. *Sci. Res. Essays* 6:1697–1708.
- Appelbaum J, Bany J (1979). Shadow effect of adjacent solar collectors in large scale systems. *Solar Energy* 23:497-507.
- Armenta C, Vorobieff P, Mammoli A (2011). Summer off-peak performance enhancement for rows of fixed solar thermal collectors using flat reflective surfaces. *Solar Energy* 85: 2041-2052.
- Bird RE, Hulstrom RL, Lewis LJ (1983). Terrestrial solar spectral data sets. *Solar Energy* 30:563-573.
- Chong KK, Wong CW (2009). General formula for on-axis sun-tracking system and its application in improving tracking accuracy of solar collector. *Solar Energy* 83:298-305.
- David A J (2011). Compensation for differential energy balance across a building incorporating solar energy systems. *Energy Build.* 43:1105-1112.
- Dole S (1962). The gravitational concentration of particles in space near the earth. *Planet. Space Sci.* 9:541-553.
- Goswami DY, Kreider JF (2000). 'Principles of solar engineering.' (Taylor & Francis).
- Guo M, Wang Z, Zhang J, Sun F, Zhang X (2012). Determination of the angular parameters in the general altitude" azimuth tracking angle formulas for a heliostat with a mirror-pivot offset based on experimental tracking data. *Solar Energy* 86:941-950.
- He W, Zhang Y, Ji J (2011). Comparative experiment study on photovoltaic and thermal solar system under natural circulation of water. *Appl. Therm. Eng.* 31:3369-3376.
- Joe SC (2005). Performance of a concentrating photovoltaic/thermal solar collector. *Solar Energy* 78:211-222.
- Liu BYH, Jordan RC (1960). The interrelationship and characteristic distribution of direct, diffuse and total solar radiation. *Solar Energy* 4:1-19.
- Muhammad-Sukki F, Ramirez-Iniguez R, Abu-Bakar SH, McMeekin SG,

- Stewart BG (2011). An evaluation of the installation of solar photovoltaic in residential houses in Malaysia: Past, present, and future. *Energy Pol.* 39:7975-7987.
- Mustaffa MT, Yeoh FLH (2011). A prototype of a solar-tracking power-generating system. *Int. J. Ambient Energy* 32:134-145.
- Ozbalta TG, Kartal S (2010). Heat gain through Trombe wall using solar energy in a cold region of Turkey. *Sci. Res. Essays* 5:2768-2778.
- Partain LD, Fraas LM (2011). 'Solar Cells and Their Applications.' (John Wiley & Sons).
- Shibayama M, Wiegand CL (1985). View azimuth and zenith, and solar angle effects on wheat canopy reflectance. *Rem. Sens. Environ.* 18:91-103.
- Simalenga TE, Maliwichi LL (2011). Promotion of household renewable energy technologies in rural communities: Challenges and experiences in Sub-Saharan Africa. *Sci. Res. Essays* 6:5650-5657.
- Ucar A, Inalli M (2008). Thermal and economic comparisons of solar heating systems with seasonal storage used in building heating. *Renew. Energy* 33:2532-2539.
- Yoo SH, Manz H (2011). Available remodeling simulation for a BIPV as a shading device. *Solar Energy Mater. Solar Cells* 95:394:397.